

## LIGHT TYPE PLIABLE CORRUGATED CONDUIT PLASTER






EASYFLEX® is used for applications with light mechanical requirements. It is ideal for installation within or under the plaster.

The conduit is produced in Beige RAL 9001, from specially stabilized, self self-extinguishing, highly resistant to flame and corrosion U-PVC.




This corrugated conduit is very flexible while maintaining its original diameter.

The specially designed internal spirals ensure minimal friction to the electrical wires and thus significantly reducing the installation time.

The classification code according to EN 61386.22 is 2221; corresponding in resistance to compression force of >320N, impact strength of >1Joule for installations at temperatures -5°C up to +60°C.

Resistance to compression	Temperature resistance	Self-extinguishing
		
320N/ 5cm		
	Colour	Packaging
		
	RAL 9001	



Reference	Type	 (mm)	 (mm)	 (m)
<a href="#">45110011.11</a>	ø11	15,9	12,4	50/200 M
<a href="#">45110013.11</a>	ø13,5	18,6	14,4	50/200 M
<a href="#">45110016.11</a>	ø16	21	16,8	50/200 M
<a href="#">45110023.11</a>	ø23	28,3	23,5	25/100 M
<a href="#">45110029.11</a>	ø29	34,2	29,5	25/100 M

The tolerances and measurements are according to DIN 49018