

LOGO! TD TEXTDISPLAY, 6 LINES, 3 BACKGROUND COLORS 2
ETHERNET PORTS ACCESSORIES, FOR LOGO! 8



General information

Suitability for use Can be used with LOGO! 8 and higher

Display

Design of display FSTN

graphics-enabled No

Line display

- Number of lines 6
- Number of characters per line 20

Backlighting

- Type of backlighting LED

Control elements

Keyboard fonts

- Keys with LED No
- System keys Yes
 - Number of configurable system keys 0
- Numeric/alphabetical input
 - Numeric keyboard No
 - alphanumeric keyboard No

Installation type/mounting	
Wall mounting/direct mounting possible	No
Supply voltage	
Type of supply voltage	AC/DC
Rated value (DC)	12 V; 12 V DC, 12/24 V AC/DC
permissible range, lower limit (DC)	10.2 V
permissible range, upper limit (DC)	28.8 V
Power loss	
Power loss, typ.	1.8 W; Typical
Digital inputs	
Number of digital inputs	0
Interfaces	
Number of industrial Ethernet interfaces	2
Number of RS 232 interfaces	0
Number of other interfaces	0
Interrupts/diagnostics/status information	
Diagnostic functions	No
Diagnostics indication LED	
<ul style="list-style-type: none"> Status indicator digital input (green) 	No
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
FM approval	Yes
KC approval	Yes
Marine approval	
<ul style="list-style-type: none"> American Bureau of Shipping (ABS) 	Yes
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. 	0 °C
<ul style="list-style-type: none"> max. 	55 °C
Accessories	
belongs to product	LOGO!
Mechanics/material	
Design of housing	plastic
Dimensions	
Width	128.2 mm
Height	86 mm
Depth	38.7 mm

Weights

Weight, approx.	220 g
-----------------	-------

Scope of supply

Delivery quantity in pieces	1
-----------------------------	---

last modified:	07/06/2016
-----------------------	------------