

## SIMATIC S7-1200 basic controller

Central processing units  
Standard CPUs

### CPU 1214C

#### Overview



- The compact high-performance CPU
- With 24 integral input/outputs
- Expandable by:
  - 1 signal board (SB) or communication board (CB)
  - 8 signal modules (SM)
  - Max. 3 communication modules (CM)

#### Technical specifications

Article number	6ES7214-1BG40-0XB0	6ES7214-1AG40-0XB0	6ES7214-1HG40-0XB0
	CPU 1214C, AC/DC/RELAY, 14DI/10DO/2AI	CPU 1214C, DC/DC/DC, 14DI/10DO/2AI	CPU 1214C, DC/DC/RELAY, 14DI/10DO/2AI
<b>Product type designation</b>			
<b>General information</b>			
<b>Engineering with</b>			
• Programming package	STEP 7 V13 SP1 or higher	STEP 7 V13 SP1 or higher	STEP 7 V13 SP1 or higher
<b>Supply voltage</b>			
Rated value (DC)		Yes	Yes
• 24 V DC			
Rated value (AC)	Yes		
• 120 V AC	Yes		
• 230 V AC	Yes		
<b>Encoder supply</b>			
<b>24 V encoder supply</b>			
• 24 V		L+ minus 4 V DC min.	L+ minus 4 V DC min.
<b>Power losses</b>			
Power loss, typ.	14 W	12 W	12 W
<b>Memory</b>			
<b>Work memory</b>			
• Integrated	100 kbyte	100 kbyte	100 kbyte
<b>Load memory</b>			
• Integrated	4 Mbyte	4 Mbyte	4 Mbyte
• Plug-in (SIMATIC Memory Card), max.	with SIMATIC memory card	with SIMATIC memory card	with SIMATIC memory card
<b>Backup</b>			
• without battery	Yes	Yes	Yes
<b>CPU processing times</b>			
for bit operations, typ.	0.085 µs; / instruction	0.085 µs; / instruction	0.085 µs; / instruction
for word operations, typ.	1.7 µs; / instruction	1.7 µs; / instruction	1.7 µs; / instruction
for floating point arithmetic, typ.	2.5 µs; / instruction	2.5 µs; / instruction	2.5 µs; / instruction
<b>Data areas and their retentivity</b>			
<b>Flag</b>			
• Number, max.	8 kbyte; Size of bit memory address area	8 kbyte; Size of bit memory address area	8 kbyte; Size of bit memory address area

# SIMATIC S7-1200 basic controller

Central processing units  
Standard CPUs

CPU 1214C

**Technical specifications** (continued)

Article number	<b>6ES7214-1BG40-0XB0</b> CPU 1214C, AC/DC/RELAY, 14DI/10DO/2AI	<b>6ES7214-1AG40-0XB0</b> CPU 1214C, DC/DC/DC, 14DI/10DO/2AI	<b>6ES7214-1HG40-0XB0</b> CPU 1214C, DC/DC/RELAY, 14DI/10DO/2AI
<b>Process image</b>			
• Inputs, adjustable	1 kbyte	1 kbyte	1 kbyte
• Outputs, adjustable	1 kbyte	1 kbyte	1 kbyte
<b>Time of day</b>			
<b>Clock</b>			
• Hardware clock (real-time clock)	Yes	Yes	Yes
<b>Digital inputs</b>			
Number of digital inputs	14; Integrated	14; Integrated	14; Integrated
• of which, inputs usable for technological functions	6; HSC (High Speed Counting)	6; HSC (High Speed Counting)	6; HSC (High Speed Counting)
<b>Digital outputs</b>			
Number of digital outputs	10; Relays	10	10; Relays
• of which high-speed outputs		4; 100 kHz Pulse Train Output	
<b>Analog inputs</b>			
Integrated channels (AI)	2; 0 to 10 V	2; 0 to 10 V	2; 0 to 10 V
<b>Input ranges</b>			
• Voltage	Yes	Yes	Yes
<b>1st interface</b>			
Interface type	PROFINET	PROFINET	PROFINET
Physics	Ethernet	Ethernet	Ethernet
<b>Functionality</b>			
• PROFINET IO Device	Yes	Yes	Yes
• PROFINET IO Controller	Yes	Yes	Yes
<b>Communication functions</b>			
<b>S7 communication</b>			
• supported	Yes	Yes	Yes
<b>Open IE communication</b>			
• TCP/IP	Yes	Yes	Yes
• ISO-on-TCP (RFC1006)	Yes	Yes	Yes
• UDP	Yes	Yes	Yes
<b>Web server</b>			
• supported	Yes	Yes	Yes
<b>Number of connections</b>			
• overall	16; dynamically	16; dynamically	16; dynamically
<b>Integrated Functions</b>			
Number of counters	6	6	6
Counter frequency (counter) max.	100 kHz	100 kHz	100 kHz
Frequency meter	Yes	Yes	Yes
controlled positioning	Yes	Yes	Yes
PID controller	Yes	Yes	Yes
Number of alarm inputs	4	4	4
Number of pulse outputs		4	
Limit frequency (pulse)		100 kHz	
<b>Ambient conditions</b>			
<b>Ambient temperature in operation</b>			
• Min.	-20 °C	-20 °C	-20 °C
• max.	60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical	60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical	60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical
<b>Pollutant concentrations</b>			
- SO <sub>2</sub> at RH < 60% without condensation	SO <sub>2</sub> : < 0.5 ppm; H <sub>2</sub> S: < 0.1 ppm; RH < 60% condensation-free	SO <sub>2</sub> : < 0.5 ppm; H <sub>2</sub> S: < 0.1 ppm; RH < 60% condensation-free	SO <sub>2</sub> : < 0.5 ppm; H <sub>2</sub> S: < 0.1 ppm; RH < 60% condensation-free

**SIMATIC S7-1200 basic controller**Central processing units  
Standard CPUs**CPU 1214C****Technical specifications** (continued)

Article number	<b>6ES7214-1BG40-0XB0</b> CPU 1214C, AC/DC/RELAY, 14DI/10DO/2AI	<b>6ES7214-1AG40-0XB0</b> CPU 1214C, DC/DC/DC, 14DI/10DO/2AI	<b>6ES7214-1HG40-0XB0</b> CPU 1214C, DC/DC/RELAY, 14DI/10DO/2AI
<b>Configuration</b>			
<b>programming</b>			
<b>Programming language</b>			
- LAD	Yes	Yes	Yes
- FBD	Yes	Yes	Yes
- SCL	Yes	Yes	Yes
<b>Dimensions</b>			
Width	110 mm	110 mm	110 mm
Height	100 mm	100 mm	100 mm
Depth	75 mm	75 mm	75 mm
<b>Weights</b>			
Weight, approx.	455 g	415 g	435 g

**Ordering data****Article No.****Article No.**

<b>CPU 1214C</b>	<b>Article No.</b>	<b>Article No.</b>
<b>Compact CPU, AC/DC/relay;</b> integral program/data memory 100 KB, load memory 2 MB; wide-range power supply 85 ... 264 V AC; Boolean execution times 0.1 µs per operation; 14 digital inputs, 10 digital outputs (relays), 2 analog inputs; expandable by up to 3 communication modules, 8 signal modules and 1 signal board/communication board; digital inputs can be used as HSC at 100 kHz	<b>6ES7214-1BG40-0XB0</b>	<b>SB 1221 signal board</b> 4 inputs, 5 V DC, 200 kHz 4 inputs, 24 V DC, 200 kHz
<b>Compact CPU, DC/DC/DC;</b> integrated program/data memory 100 KB, load memory 2 MB; power supply 24 V DC; Boolean execution times 0.1 µs per operation; 14 digital inputs, 10 digital outputs, 2 analog inputs; expandable by up to 3 communication modules, 8 signal modules, and 1 signal board/communication board; digital inputs can be used as HSC at 100 kHz, 24 V DC digital outputs can be used as pulse outputs (PTO) or pulse-width modulated outputs (PWM) at 100 kHz	<b>6ES7214-1AG40-0XB0</b>	<b>SB 1222 signal board</b> 4 outputs, 5 V DC, 0.1 A, 200 kHz 4 outputs, 24 V DC, 0.1 A, 200 kHz
<b>Compact CPU, DC/DC/relay;</b> integrated program/data memory 100 KB, load memory 2 MB; power supply 24 V DC; Boolean execution times 0.1 µs per operation; 14 digital inputs, 10 digital outputs (relay), 2 analog inputs; expandable by up to 3 communication modules, 8 signal modules, and 1 signal board/communication board; digital inputs can be used as HSC at 100 kHz	<b>6ES7214-1HG40-0XB0</b>	<b>SB 1223 signal board</b> 2 inputs, 24 V DC, IEC type 1 current sinking; 2 x 24 V DC transistor outputs, 0.5 A, 5 W; can be used as HSC at up to 30 kHz
		<b>SB 1223 signal board</b> 2 inputs, 5 V DC, 200 kHz 2 outputs 5 V DC, 0.1 A, 200 kHz
		<b>SB 1223 signal board</b> 2 inputs, 24 V DC, 200 kHz 2 outputs 24 V DC, 0.1 A, 200 kHz
		<b>SB 1231 signal board</b> 1 analog input, ±10 V with 12 bits or 0 ... 20 mA with 11 bits
		<b>Thermocouple signal board SB 1231</b> 1 input +/- 80 mV, resolution 15 bits + sign, thermocouples type J, K
		<b>RTD signal board SB 1231</b> 1 input for resistance temperature sensors Pt 100, Pt 200, Pt 500, Pt 1000, resolution 15 bits + sign
		<b>SB 1232 signal board</b> 1 analog output, ±10 V with 12 bits or 0 to 20 mA with 11 bits
		<b>Communication board CB 1241 RS 485</b> for point-to-point connection, with 1 RS 485 interface
		<b>SB 1221 signal board</b> 4 inputs, 5 V DC, 200 kHz 4 inputs, 24 V DC, 200 kHz
		<b>SB 1222 signal board</b> 4 outputs, 5 V DC, 0.1 A, 200 kHz 4 outputs, 24 V DC, 0.1 A, 200 kHz
		<b>SB 1223 signal board</b> 2 inputs, 24 V DC, IEC type 1 current sinking; 2 x 24 V DC transistor outputs, 0.5 A, 5 W; can be used as HSC at up to 30 kHz
		<b>SB 1231 signal board</b> 1 analog input, ±10 V with 12 bits or 0 ... 20 mA with 11 bits
		<b>Thermocouple signal board SB 1231</b> 1 input +/- 80 mV, resolution 15 bits + sign, thermocouples type J, K
		<b>RTD signal board SB 1231</b> 1 input for resistance temperature sensors Pt 100, Pt 200, Pt 500, Pt 1000, resolution 15 bits + sign
		<b>SB 1232 signal board</b> 1 analog output, ±10 V with 12 bits or 0 to 20 mA with 11 bits
		<b>Communication board CB 1241 RS 485</b> for point-to-point connection, with 1 RS 485 interface
		<b>SB 1221 signal board</b> 4 inputs, 5 V DC, 200 kHz 4 inputs, 24 V DC, 200 kHz
		<b>SB 1222 signal board</b> 4 outputs, 5 V DC, 0.1 A, 200 kHz 4 outputs, 24 V DC, 0.1 A, 200 kHz
		<b>SB 1223 signal board</b> 2 inputs, 24 V DC, IEC type 1 current sinking; 2 x 24 V DC transistor outputs, 0.5 A, 5 W; can be used as HSC at up to 30 kHz
		<b>SB 1231 signal board</b> 1 analog input, ±10 V with 12 bits or 0 ... 20 mA with 11 bits
		<b>Thermocouple signal board SB 1231</b> 1 input +/- 80 mV, resolution 15 bits + sign, thermocouples type J, K
		<b>RTD signal board SB 1231</b> 1 input for resistance temperature sensors Pt 100, Pt 200, Pt 500, Pt 1000, resolution 15 bits + sign
		<b>SB 1232 signal board</b> 1 analog output, ±10 V with 12 bits or 0 to 20 mA with 11 bits
		<b>Communication board CB 1241 RS 485</b> for point-to-point connection, with 1 RS 485 interface
		<b>SB 1221 signal board</b> 4 inputs, 5 V DC, 200 kHz 4 inputs, 24 V DC, 200 kHz
		<b>SB 1222 signal board</b> 4 outputs, 5 V DC, 0.1 A, 200 kHz 4 outputs, 24 V DC, 0.1 A, 200 kHz
		<b>SB 1223 signal board</b> 2 inputs, 24 V DC, IEC type 1 current sinking; 2 x 24 V DC transistor outputs, 0.5 A, 5 W; can be used as HSC at up to 30 kHz
		<b>SB 1231 signal board</b> 1 analog input, ±10 V with 12 bits or 0 ... 20 mA with 11 bits
		<b>Thermocouple signal board SB 1231</b> 1 input +/- 80 mV, resolution 15 bits + sign, thermocouples type J, K
		<b>RTD signal board SB 1231</b> 1 input for resistance temperature sensors Pt 100, Pt 200, Pt 500, Pt 1000, resolution 15 bits + sign
		<b>SB 1232 signal board</b> 1 analog output, ±10 V with 12 bits or 0 to 20 mA with 11 bits
		<b>Communication board CB 1241 RS 485</b> for point-to-point connection, with 1 RS 485 interface

**SIMATIC S7-1200 basic controller**Central processing units  
Standard CPUs

CPU 1214C

Ordering data	Article No.	Article No.
<b>Digital input simulator Simulator Module SIM 1274 (optional)</b> 14 input switches, for CPU 1214C / CPU 1215C	<b>6ES7274-1XH30-0XA0</b>	<b>STEP 7 Professional / Basic V13 SP1</b> Target system: SIMATIC S7-1200, S7-1500, S7-300, S7-400, WinAC Requirement: Windows 7 Professional SP1 (64-bit), Windows 7 Enterprise SP1 (64-bit), Windows 7 Ultimate SP1 (64-bit), Windows 8.1 (64-bit), Windows 8.1 Professional (64-bit), Windows 8.1 Enterprise (64-bit), Windows Server 2008 R2 StdE (full installation), Windows Server 2012 StdE (full installation) Available in: German, English, Chinese, Italian, French, Spanish  STEP 7 Professional V13 SP1, floating license  STEP 7 Professional V13 SP1, floating license, software download incl. license key <sup>1)</sup>  Email address required for delivery  STEP 7 Basic V13 SP1, floating license  STEP 7 Basic V13 SP1, floating license, software download incl. license key <sup>1)</sup>  Email address required for delivery
<b>Analog input simulator Simulator Module SIM 1274 (optional)</b> 2 potentiometers	<b>6ES7274-1XA30-0XA0</b>	
<b>SIMATIC Memory Card (optional)</b> 4 MB	<b>6ES7954-8LC02-0AA0</b>	
12 MB	<b>6ES7954-8LE02-0AA0</b>	
24 MB	<b>6ES7954-8LF02-0AA0</b>	
256 MB	<b>6ES7954-8LL02-0AA0</b>	
2 GB	<b>6ES7954-8LP01-0AA0</b>	
<b>Extension cable for two-tier configuration</b> for connecting digital/analog signal modules; length 2 m	<b>6ES7290-6AA30-0XA0</b>	
<b>Terminal block (spare part)</b> for CPU 1214C For DI, with 20 screws, tin-plated; 4 units	<b>6ES7292-1AV30-0XA0</b>	
For DO, with 12 screws, tin-plated; 4 units	<b>6ES7292-1AM30-0XA0</b>	
For AI, with 3 screws, tin-plated; 4 units	<b>6ES7292-1BC30-0XA0</b>	
<b>RJ45 cable grip</b> 4 items per pack Single port	<b>6ES7290-3AA30-0XA0</b>	
<b>Front flap set (spare part)</b> for CPU 1214C	<b>6ES7291-1AB30-0XA0</b>	

<sup>1)</sup> For up-to-date information and download availability, see:  
<http://www.siemens.com/tia-online-software-delivery>