

UNITEST DR 705

Rotary Field Indicator

Key Functions

- Indication of the three phases via glow lamp
- Indication of the phase rotation direction via glow lamp

General Information

- Swift determination of the phase sequence in three-phase networks

Technical Data

Voltage Range	80...440 V
Current Consumption (at Voltage)	< 3.5 mA (440 V)
Frequency Range	50...60 Hz
Operation Time	continuous
Pollution Degree	2
Measurement category	CAT III, 300 V
Safety Complying with	IEC61010 / EN61010 IEC61557-7 / EN61557-7
Power Supply	from unit under test
Dimensions	124 x 61 x 27 mm
Weight	approx. 200 g



Scope of Supply:

- 1 pc UNITEST DR 705
- 3 pc Test Probes
- 1 pc Crocodile Clamp
- 1 pc Instruction Manual



Accessories:

Accessory Set UNIdreh
Cat. No. 1324



Carrying Case
Cat. No. 1150



Clamp-type test probe for Current
Tracks
Cat. No. 391511 (red)
Cat. No. 391512 (black)

Order Information:

Description	Cat. No.
UNITEST DR 705	9043
Accessory Set UNIdreh	1324
Carrying Case	1150
Clamp-type test probe for Current Tracks	
red	391511
black	391512