

	
<ul style="list-style-type: none"> • Reliable and fast starting • Suitable for temperatures from -20°C to +80°C • For single and twin lamp operation • Testhouse approved and ENEC/VDE marked 	

Code	Description	Watt	Volt	Lamp Type	Circuit	Packing Qty
FS Standard Starters						
0024454	FS-11	4, 6, 8, 13W	220-240V	T5	Single	1000
		14, 15, 16, 18, 25, 36, 38, 58W	220-240V	T8	Single	
		20, 40, 65, 80W	220-240V	T12	Single	
		22, 32, 40, 60W	220-240V	Circline	Single	
		18, 24, 36W	220-240V	CF-L	Single	
0024456	FS-11	As Above	220-240V	As Above	Single	1000
		Industrial Pack				
0024455	FS-22	4, 6, 8W	120V	T12	Single	1000
		4, 6, 8W	230V	T12	Twin	
		14, 15, 18W	120V	T8	Single	
		14, 15, 18W	230V	T8	Twin	
		20W	120V	T12	Single	
		20W	230V	T12	Twin	
		22W	120V	Circline	Single	
		22W	230V	Circline	Twin	
		18W	120V	CF-L	Single	
		18W	230V	CF-L	Twin	
		18W	120V	CF-F	Single	
		18W	230V	CF-F	Twin	
		0024457	FS-22	As Above	As Above	
Industrial Pack						