


SKINTOP® MS

SKINTOP® MS, brass cable gland with maximum reliability, in areas where mechanical and chemical stability are critical



Variety of approval certifications



Temperature-resistant



Robust



Optimum strain relief



Corrosion-resistant



Good chemical resistance

Benefits

Maximum reliability

Optimum strain relief

Wide, variable clamping ranges

Application range

In areas where mechanical and chemical stability are critical

Chemical industry

Measurement and control technology

Machine and equipment manufacturing

Plant engineering

SKINTOP® MS

Product Make-up

PG connection thread

Note

Counter nut to be used: SKINDICHT® SM

Refer to SKINTOP® PG accessories for suitable accessories

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable screw gland
Caution:	Refer to Appendix T21 for the installation dimensions and torques
Material:	Body: nickel-plated brass Insert: polyamide Sealing ring: CR O-ring: NBR
Protection rating:	IP 68 - 10 bar
Temperature range:	dynamic -25°C up to + 100°C static -40°C up to +100°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.

* Prices are net prices without VAT and surcharges. Sale to business customers.

**SKINTOP® MS**

Article number	Article designation / size	Clamping range ØF (mm)	SW wrench size mm	Overall length, C (mm)	Thread length, D (mm)
SKINTOP® MS					
52015700	MS 7	2 - 6.5	14	25	5
52015710	MS 9	4 - 8	17	29	6
52015720	MS 11	4 - 10	20	32	6
52015730	MS 13,5	5 - 12	22	34	6.5
52015740	MS 16	8 - 14	24	35	6.5
52015750	MS 21	11 - 18	30	40	7
52015760	MS 29	16 - 25	40	48	8
52015765	MS 36	19 - 32	50	62	15
52015766	MS 42	28 - 38	57	62	15
52015767	MS 48	34 - 44	64	62	15

Last Update (12.08.2016)

©2016 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16