

## SIMATIC S7-1200 basic controller

I/O modules

Analog modules

### SM 1231 analog input modules

#### Overview



- Analog inputs for SIMATIC S7-1200
- With extremely short conversion times
- For connecting analog sensors without additional amplifiers
- For solving even more complex automation tasks

3

#### Technical specifications

Article number	<b>6ES7231-4HD32-0XB0</b> ANALOG INPUT SM 1231, 4AI	<b>6ES7231-4HF32-0XB0</b> ANALOG INPUT SM 1231, 8AI	<b>6ES7231-5ND32-0XB0</b> ANALOG INPUT SM 1231, 4AI 16BIT
<b>Product type designation</b>			
<b>Supply voltage</b>			
Rated value (DC)			
• 24 V DC	Yes	Yes	Yes
<b>Input current</b>			
Current consumption, typ. from backplane bus 5 V DC, typ.	45 mA 80 mA	45 mA 90 mA	65 mA 80 mA
<b>Power losses</b>			
Power loss, typ.	1.5 W	1.5 W	1.8 W
<b>Analog inputs</b>			
Number of analog inputs	4; Current or voltage differential inputs	8; Current or voltage differential inputs	4; Current or voltage differential inputs
permissible input frequency for current input (destruction limit), max.	± 35 V	± 35 V	± 35 V
permissible input voltage for voltage input (destruction limit), max.	35 V	35 V	35 V
permissible input current for voltage input (destruction limit), max.	40 mA	40 mA	40 mA
permissible input current for current input (destruction limit), max.	40 mA	40 mA	40 mA
Cycle time (all channels) max.	625 µs	625 µs	625 µs
<b>Input ranges</b>			
• Voltage	Yes; ±10V, ±5V, ±2.5V	Yes; ±10V, ±5V, ±2.5V	Yes; ±10V, ±5V, ±2.5V or ±1.25V
• Current	Yes; 4 to 20 mA, 0 to 20 mA	Yes; 4 to 20 mA, 0 to 20 mA	Yes; 4 to 20 mA, 0 to 20 mA
• Thermocouple	No	No	No
• Resistance thermometer	No	No	No
• Resistance	No	Yes	Yes
<b>Input ranges (rated values), voltages</b>			
• -1.25 V to +1.25 V			Yes
• -10 V to +10 V	Yes	Yes	Yes
• Input resistance (-10 V to +10 V)	≥9 MΩ	≥9 MΩ	≥9 MΩ
• -2.5 V to +2.5 V	Yes	Yes	Yes
• Input resistance (-2.5 V to +2.5 V)	≥9 MΩ	≥9 MΩ	≥9 MΩ
• -5 V to +5 V	Yes	Yes	Yes
• Input resistance (-5 V to +5 V)	≥9 MΩ	≥9 MΩ	≥9 MΩ

**Technical specifications (continued)**

Article number	<b>6ES7231-4HD32-0XB0</b> ANALOG INPUT SM 1231, 4AI	<b>6ES7231-4HF32-0XB0</b> ANALOG INPUT SM 1231, 8AI	<b>6ES7231-5ND32-0XB0</b> ANALOG INPUT SM 1231, 4AI 16BIT
<b>Input ranges (rated values), currents</b>			
• 0 to 20 mA	Yes	Yes	Yes
• Input resistance (0 to 20 mA)	280 Ω	280 Ω	
• 4 mA to 20 mA	Yes		Yes
<b>Thermocouple (TC)</b>			
<b>Temperature compensation</b>			
- Parameterizable		No	
<b>Analog outputs</b>			
Number of analog outputs	0	0	0
<b>Analog value creation</b>			
<b>Integration and conversion time/ resolution per channel</b>			
• Resolution with overrange (bit including sign), max.	12 bit; + sign	12 bit; + sign	15 bit; + sign
• Integration time, parameterizable	Yes	Yes	Yes
• Interference voltage suppression for interference frequency f1 in Hz	40 dB, DC to 60 V for interference frequency 50 / 60 Hz	40 dB, DC to 60 V for interference frequency 50 / 60 Hz	40 dB, DC to 60 V for interference frequency 50 / 60 Hz
<b>Smoothing of measured values</b>			
• Parameterizable	Yes	Yes	Yes
• Step: None	Yes	Yes	Yes
• Step: low	Yes	Yes	Yes
• Step: Medium	Yes	Yes	Yes
• Step: High	Yes	Yes	Yes
<b>Errors/accuracies</b>			
Temperature error (relative to input range), (+/-)	25 °C ±0.1%, to 55 °C ±0.2% total measurement range	25 °C ±0.1%, to 55 °C ±0.2% total measurement range	25 °C ±0.1% / ±0.3% total measurement range
<b>Basic error limit (operational limit at 25 °C)</b>			
• Voltage, relative to input area, (+/-)	0.1 %	0.1 %	0.1 %
• Current, relative to input area, (+/-)	0.1 %	0.1 %	0.1 %
<b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1\%)</math>, f1 = interference frequency</b>			
• common mode voltage, max.	12 V	12 V	12 V
<b>Interrupts/diagnostics/ status information</b>			
<b>Alarms</b>			
• Alarms	Yes	Yes	Yes
• Diagnostic alarm	Yes	Yes	Yes
<b>Diagnostic messages</b>			
• Diagnostic functions	Yes	Yes	Yes
• Monitoring the supply voltage	Yes	Yes	Yes
• Wire break	Yes	Yes	Yes
<b>Diagnostics indication LED</b>			
• for status of the inputs	Yes	Yes	Yes
• for maintenance	Yes	Yes	Yes
<b>Galvanic isolation analog outputs</b>			
• between the channels and the power supply of the electronics	No	No	No
<b>Degree and class of protection</b>			
Degree of protection to EN 60529			
• IP20	Yes	Yes	Yes

**SIMATIC S7-1200 basic controller**

I/O modules

Analog modules

**SM 1231 analog input modules****Technical specifications (continued)**

Article number	<b>6ES7231-4HD32-0XB0</b> ANALOG INPUT SM 1231, 4AI	<b>6ES7231-4HF32-0XB0</b> ANALOG INPUT SM 1231, 8AI	<b>6ES7231-5ND32-0XB0</b> ANALOG INPUT SM 1231, 4AI 16BIT
<b>Standards, approvals, certificates</b>			
CE mark	Yes	Yes	Yes
CSA approval	Yes	Yes	Yes
FM approval	Yes	Yes	Yes
RCM (formerly C-TICK)	Yes	Yes	Yes
<b>Marine approval</b>			
• Marine approval	Yes	Yes	Yes
<b>Highest safety class achievable in safety mode</b>			
• SIL according to IEC 61508		none	none
<b>Ambient conditions</b>			
<b>Free fall</b>			
• Drop height, max. (in packaging)	0.3 m; five times, in dispatch package	0.3 m; five times, in dispatch package	0.3 m; five times, in dispatch package
<b>Ambient temperature in operation</b>			
• Permissible temperature range	-20 °C to +60 °C horizontal mounting, -20 °C to 50 °C vertical mounting, 95% humidity, non-condensing	-20 °C to +60 °C horizontal mounting, -20 °C to 50 °C vertical mounting, 95% humidity, non-condensing	-20 °C to +60 °C horizontal mounting, -20 °C to 50 °C vertical mounting, 95% humidity, non-condensing
• Min.	-20 °C	-20 °C	-20 °C
• max.	60 °C	60 °C	60 °C
<b>Storage/transport temperature</b>			
• Min.	-40 °C	-40 °C	-40 °C
• max.	70 °C	70 °C	70 °C
<b>Air pressure acc. to IEC 60068-2-13</b>			
• Operation, min.	795 hPa	795 hPa	795 hPa
• Operation, max.	1 080 hPa	1 080 hPa	1 080 hPa
• Storage/transport, min.	660 hPa	660 hPa	660 hPa
• Storage/transport, max.	1 080 hPa	1 080 hPa	1 080 hPa
<b>Relative humidity</b>			
• Permissible range (without condensation) at 25 °C	95 %	95 %	95 %
<b>Pollutant concentrations</b>			
- SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
<b>Connection method</b>			
required front connector	Yes	Yes	Yes
<b>Mechanics/material</b>			
Type of housing (front)			
• plastic	Yes	Yes	Yes
<b>Dimensions</b>			
Width	45 mm	45 mm	45 mm
Height	100 mm	100 mm	100 mm
Depth	75 mm	75 mm	75 mm
<b>Weights</b>			
Weight, approx.	180 g	180 g	180 g

Ordering data	Article No.	Article No.
<b>SM 1231 analog input signal module</b>		
4 analog inputs, ± 10V, ± 5V, ± 2.5V, or 0 ... 20 mA, 16 bits	<b>6ES7231-5ND32-0XB0</b>	<b>Extension cable for two-tier configuration</b>
for connecting digital/analog signal modules; length 2 m		<b>6ES7290-6AA30-0XA0</b>
4 analog inputs, ± 10V, ± 5V, ± 2.5V, or 0 ... 20 mA, 12 bits + sign	<b>6ES7231-4HD32-0XB0</b>	<b>Terminal block (spare part)</b>
8 analog inputs, ± 10V, ± 5V, ± 2.5V, or 0 ... 20 mA, 12 bits + sign	<b>6ES7231-4HF32-0XB0</b>	for 8/16-channel analog signal modules with 7 screws, gold-plated; 4 pcs.
		<b>6ES7292-1BG30-0XA0</b>
		<b>Front flap set (spare part)</b>
		for 8/16-channel signal modules
		<b>6ES7291-1BA30-0XA0</b>