



UT-C04

- Insulated Alligator Clip with Banana Type Jack;
- Alligator Clip Length: 82mm, Maximum Opening: 33mm;
- CAT III 1000V 10A



UT-C07

- Extendable Probe makes measurement more convenient;
- Standard banana interface could connect to multiple types of test lead adapters;
- CAT III 1000V, CAT IV 600V 5A



UT-L13

- Double Insulation, UL authenticated test cable, Ø4mm standard probe could connect to standard banana interface;
- Removable insulation cap is used for probe protection;
- Cable length: 1200mm, probe body length: 128mm, probe length: 18mm;
- CAT III 1000V 10A



UT-L23

- Double Insulation, CE authenticated, connector with protection cover, to ensure effective connectivity;
- 150 core, cable length: 1230mm, Probe Body Length: 130mm, Probe Length: 18mm;
- Temperature: 0°C~50°C
- CAT III 1000V, CAT IV 600V 10A



UT-D03

- Standard interface converter cable;
- Effective connection distance: 1000mm;
- No driver needed, applicable to convert connection between test leads and PC.



UT-D04

- Infrared USB Connection Cable, applicable to data transferring for bench-type and handheld PC;
- Effective connection distance: 1500mm;
- Applicable to UT71A, UT71B, UT71C, UT71D, UT71E, etc.