

Specifications	Range
Model	
DC Voltage (V)	4V/40V/400V/1000V
AC Voltage (V)	40mV/400mV/4V/40V/400V/1000V
DC Current (A)	400μA/4000μA/40mA/400mA/4A/10A
AC Current (A)	400μA/4000μA/40mA/400mA/4A/10A
Resistance (Ω)	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ
Capacitance (F)	10nF/100nF/1000nF/10μF/100μF
Frequency (Hz)	10Hz ~ 1MHz
Temperature (°C)	-40°C ~ 537°C
Temperature (°F)	-40°F ~ 998°F
Features	
Display Count	
Auto Range	
Diode	
Auto Power Off	
Continuity Buzzer	
Low Battery Indication	
Data Hold	
MAX/MIN	
RS-232	
USB Interface	
LCD Backlight	
Input Protection	
Input Impedance for DCV	Around 10MΩ
Dwell	4CYL/6CYL/8CYL
Tach	4CYL/6CYL/8CYL
General Characteristic	
Power	9V Battery (6F22)
LCD Size	65mm X 43mm
Product Color	Red and Grey
Product Net Weight	370g
Product Size	180mm X 87mm X 47mm
Standard Accessories	Battery, Test Lead, Alligator Clip, RS-232 Interface Cable, PC Temperature Probe, Multi-Purpose Socket
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	20 PCs
Standard Carton Measurement	465mm X 335mm X 365mm (0.057 CBM Per Standard Carton)
Standard Carton Gross Weight	15.5 Kg
Optional Accessories*	USB Interface Cable

Best Accuracy
UT109
±(0.5%+3)
±(1%+3)
±(1%+2)
±(1.2%+5)
±(1%+5)
±(3%+5)
±(0.1%+4)
±(1%+10)
±(1%+18)

3999
√
√
√
√
√
√
√
√
√
√
√
√
±(3%+5)
±(3%+5)

Software CD, Point Contact
on)