

Specifications	Range	Best Accuracy
Model		UT132B
DC Voltage (V)	200mV/2000mV/20V/200V/600V	$\pm(0.5\%+2)$
AC Voltage (V)	200V/ 600V	$\pm(1.2\%+3)$
DC Current (A)	2000 μ A/ 200mA/ 10A	$\pm (1\%+2)$
Resistance (Ω)	200 Ω / 2000 Ω / 20K Ω / 200K Ω / 2000K Ω / 20M Ω	$\pm(0.8\%+5)$
Features		
Display Count		1999
Manual Range		\checkmark
Battery Test	1.5V/ 9V	$\pm (1\%+2)$
Diode		\checkmark
Transistor		\checkmark
Continuity Buzzer		\checkmark
Low Battery Indication		\checkmark
Data Hold		\checkmark
Input Impedance for DCV	Around 10M Ω	\checkmark
General Characteristic		
Power	9V Battery (6F22)	
LCD Size	49mm X 18 mm	
Product Color	Red and Grey	
Product Net Weight	200g	
Product Size	72mm×137mm×35mm	
Standard Accessories	Battery, Test Lead, Multi-Purpose Socket	
Standard Individual Packing	Gift Box, English Manual	

Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	540mm X 365mm X 290mm (0.057CBM Per Standard Carton)
Standard Carton Gross Weight	13.8 Kg