

Specifications	Range	Best Accuracy
<b>Model</b>		<b>UT139C</b>
DC Voltage (V)	60mV/600mV/6V/60V/600V	±(0.5%+2)
AC Voltage (V)	60mV/600mV/6V/60V/600V	±(0.8%+3)
DC Current (A)	600μA/6000μA/60mA/600mA/6A/10A	± (0.7%+2)
AC Current (A)	600μA/6000μA/60mA/600mA/6A/10A	±(1%+3)
Resistance (Ω)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.8%+2)
Capacitance (F)	9.999nF/99.99nF/999.9nF/9.999μF/99.99μF/ 999.9μF/9.999mF/99.99mF	±(4.0%+5)
Frequency (Hz)	10Hz-10MHz	±(0.1%+4)
Temperature (°C)	-40 °C~1000°C	±(1.0%+3)
Temperature (°F)	-40°F~1832°F	±(1.5%+5)
<b>Features</b>		
Display Count		6000
Auto Range		√
Manual Range		√
True RMS		√
Bandwidth (Hz)		45Hz ~ 1kHz
V.F.C		√
Duty Cycle	0.1% ~ 99.9%	√
Diode		Around 3V
NCV		√
Auto Power Off	Around 15 Minutes	√

Continuity Buzzer		√
Low Battery Indication	≤2.5V	√
Data Hold		√
Relative Mode		√
MAX/MIN		√
LCD Backlight		√
Input Protection	600Vrms	√
Input Impedance for DCV	1GΩ Max	√
<b>General Characteristics</b>		
Power	AA1.5*2	
LCD Size	58mm × 36 mm	
Product Colour	Red and Grey	
Product Net Weight	370g	
Product Size	175mm x 81mm x 48.5 mm	
Standard Accessories	Battery, Test Leads, Temperature Probe	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	40 PCs	
Standard Carton Measurement	645mm×450mm×340mm (0.098CBM Per Standar Carton)	
Standard Carton Cross Weight	25.5 Kg	
<b>Optional Accessories*</b>		
Current Sensor AC/DC40A		