



Intertek

UL 61010-1
IEC 61010-2-032
EN 61010-1
EN 61010-2-033
EN 61010-2-032
EN 61326-1



■ UT203



■ UT204



■ UT204A

SPECIFICATIONS



Specifications	Range	Best Accuracy		
		UT203	UT204	UT204A
Model		UT203	UT204	UT204A
AC Current(A)	40A/400A 40A/600A	±(2.5%+5)	±(2.5%+5)	±(2.5%+5)
DC Current(A)	40A/400A 40A/600A	±(2%+3)	±(2%+3)	±(2.5%+5)
AC Voltage(V)	4V/40V/400V/600V	±(1%+5)	±(1%+5)	±(1%+5)
DC Voltage(V)	400mV/4V/40V/400V/600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	400Ω/4kΩ/40kΩ/400kΩ/ 4MΩ/40MΩ	±(1%+2)	±(1%+2)	±(1%+2)
Capacitance (F)	4nF/40nF/400nF/4μF/40μF /100μF			±(4%+3)
Frequency (Hz)	10Hz~1MHz	±(0.1%+3)	±(0.1%+3)	
	10Hz ~ 10MHz			±(0.5%+3)
	10MHz			Reference only
Temperature (°C)	-40 °C~1000°C			±(2.5%+3)

Features

Features	UT203	UT204	UT204A
Display Count	4000	4000	4000
Auto Range	✓	✓	✓
Jaw Capacity	28mm	28mm	28mm
True RMS		✓	
Duty Cycle	0.1%~99.9%	✓	✓
Diode	✓	✓	✓
Auto Power Off	✓	✓	✓
Continuity Buzzer	✓	✓	✓
Low Battery Indication	✓		✓
Data Hold	✓	✓	✓
Relative Mode	✓	✓	
Max Mode			✓
Setup	✓	✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery(6F22)
LCD Size	35.6mm × 18mm
Product Color	Red and Grey
Product Net Weight	260 g
Product Size	208mm × 76mm × 30 mm
Standard Accessories	UT203/UT204-Battery, Test Lead UT204A-Battery, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	540mm × 495mm × 335mm(0.09 CBM Per Standard Carton)
Standard Carton Gross Weight	25 Kg