



Intertek

UL 61010-1
IEC 61010-2-032
EN 61010-1
EN 61010-2-033
EN 61010-2-032
EN 61326-1



■ UT207A



■ UT208A



■ UT209A

SPECIFICATIONS



Specifications	Range	Best Accuracy		
Model		UT207A	UT208A	UT209A
AC Current(A)	40A/400A/1000A	±(2%+2)	±(2%+2)	±(2%+2)
DC Current(A)	40A/400A/1000A	±(1.5%+5)	±(1.5%+5)	±(1.5%+5)
AC Voltage(V)	400mV/4V/40V/400V/750V	±(1.2%+3)	±(1.2%+3)	±(1.2%+3)
DC Voltage(V)	400mV/4V/40V/400V/1000V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	400Ω/4kΩ/40kΩ/400kΩ/ 4MΩ/40MΩ	±(1%+2)	±(1%+2)	±(1%+2)
Capacitance (F)	4nF/40nF/400nF/4μF/40μF /100μF		±(4%+3)	
Frequency (Hz)	10Hz/100Hz/1kHz/10kHz/ 1MHz/10MHz	±(0.1%+3)	±(0.1%+3)	±(0.1%+3)
Temperature (°C)	-40°C~1000°C		±(2.5%+3)	

Features

Features	UT207A	UT208A	UT209A
Display Count	4000	4000	4000
Auto Range	✓	✓	✓
Jaw Capacity	55mm	55mm	55mm
True RMS	AC Voltage/AC Current		✓
Duty Cycle	0.1%~99.9%	✓	✓
Diode	✓	✓	✓
Auto Power Off	✓	✓	✓
Continuity Buzzer	✓	✓	✓
Low Battery Indication	✓	✓	✓
Data Hold	✓	✓	✓
LCD Backlight	✓	✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery(6LF22)
LCD Size	47mm × 30 mm
Product Color	Red and Grey
Product Net Weight	533 g
Product Size	286mm × 105mm × 45mm
Standard Accessories	UT207A/UT209A -Battery, Test Lead UT208A -Battery, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, Tool Box, English Manual
Standard Quantity Per Carton	5 PCs
Standard Carton Measurement	480mm × 372mm × 315mm (0.056 CBM Per Standard Carton)
Standard Carton Gross Weight	11 Kg