



# UT210 SERIES

## Mini Clamp Meters

UT210D (new) / UT210E



UL61010-1  
EN61010-1  
EN61010-2-032  
EN61010-2-033  
EN61326-1



■ UT210D



■ UT210E

### SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT210D	UT210E
Model			
AC Current (A)	20A/200A 2A/20A/100A	±(2.5%+8)	±(2.5%+5)
DC Current (A)	20A/200A 2A/20A/100A	±(2%+3)	±(2%+3)
AC Voltage(V)	2V/20V200V/600V	±(1%+3)	±(1%+3)
DC Voltage(V)	200mV/2V/20V200V/600V	±(0.7%+3)	±(0.7%+3)
Resistance(Ω)	10Hz/100Hz/1kHz/10kHz/60kHz	±(1%+2)	±(1%+2)
Frequency (Hz)	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.1%+4)	
Capacitance (F)	2nF/20nF/200nF/2μF/20μF/200μF/2mF/20mF	±(4%+5)	±(4%+5)
Temperature(°C)	-40~1000°C	±(1%+3)	
Temperature(°F)	-40~1832°F	±(1.5%+5)	
<b>Features</b>			
Display Count		2000	2000
Auto Range		✓	✓
Jaw Capacity		17mm	17mm
True RMS		✓	✓
Diode	Around 3.0V	✓	✓
NCV		✓	✓
Data Hold		✓	✓
MAX/MIN		✓	✓
Zero		✓	✓
LCD Backlight		✓	✓
Auto Power Off	Around 15 Minutes	✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication	≤2.5V	✓	✓
Input Protection		✓	✓
Input Impedance for DCV	≥10MΩ	✓	✓

### GENERAL CHARACTERISTICS

Power	AAA 1.5V x 2
LCD Size	39.3mm x 26.5 mm
Product Color	Red and Grey
Product Net Weight	170g
Product Size	175mm x 60mm x 33.5mm
Standard Accessories	<b>UT210D</b> -Batteries, Test Lead, Point Contact Temperature Probe <b>UT210E</b> -Batteries, Test Lead
Standard Individual Packing	Gift Box, Carrying bag, English Manual
Standard Quantity Per Carton	40PCs
Standard Carton Measurement	385X345X305mm (0.041 CBM Per Standard Carton)
Standard Carton Gross Weight	11kg