

Specifications	Range	Best Accuracy
<b>Model</b>		<b>UT71C</b>
DC Voltage (V)	400mV/4V/40V/400V/1000V	±(0.025%+5)
AC Voltage (V)	4V/40V/400V/1000V	±(0.4%+30)
DC Current (A)	400µA/4000µA/40mA/400mA/10A	± (0.1%+15)
AC Current (A)	400µA/4000µA/40mA/400mA/10A	± (0.7%+15)
Resistance (Ω)	400Ω/4KΩ/40KΩ/400KΩ/4MΩ/40MΩ	±(0.3%+8)
Capacitance (F)	40nF/400nF/4µF/40µF/400µF/4mF/40mF	±(1%+20)
Frequency (Hz)	40Hz-400MHz	±(0.01%+8)
Temperature (°C)	-40 °C ~ 1000°C	±(1%+30)
Temperature (°F)	-40°F ~ 1832°F	±(1.5%+50)
<b>Features</b>		
Display Count		39999
Auto Range		√
True RMS		√
Bandwidth (Hz)	100KHz	√
Duty Cycle	10% ~ 90%	±(1%+30)
Diode		√
Auto Power Off		√
Continuity Buzzer		√
Low Battery Indication		√
Data Hold		√
Relative Mode		√
MAX/MIN		√
Data Logging		100
USB Interface		√
Double Backlight		√
Analogue Bar Graph		√
Full Icon Display		√
Setup		√
Input Impedance for DCV	DC 400mV: Around 2.5GΩ, All Other Range : 10MΩ	√
4 - 20mA Loop	0~100%	±(1%+50)
Fused 10 A		√
Current Measurement Alarm		√
Voltage & Current AC+DC Measurement		√
<b>General Characteristic</b>		
Power	9V Battery (6F22)	
LCD Size	73mm X 50 mm	
Product Color	Red and Grey	
Product Net Weight	384g	
Product Size	200mm X 93mm X 40 mm	
Standard Accessories	Battery, Test Lead, Alligator Clip, Test Clip, USB Interface Cable, PC Software CDe, Carrying Bag, Point Contact	

Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	20 PCs
Standard Carton Measurement	530mm X 360mm X 385mm (0.073 CBM Per Standard Carton)
Standard Carton Gross Weight	22 Kg