

Wiha SoftFinish® electric.

The safe and comfortable insulated VDE screwdriver.



The right tool at a glance, thanks to the printed screw symbol on the handle end.



For slotted screws.



320N

SoftFinish® electric slotted screwdriver.

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN ISO 2380.
Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	Ø	↔	↔	↔	↔
00819	2.0	60	0.4	164	23
00820	2.5	75	0.4	179	23
00821	3.0	100	0.5	204	23
00822	3.5	100	0.6	204	23
00823	4.0	100	0.8	211	30
00824	4.5•	125	1.0	236	30
00825	4.5•	175	1.0	286	30
31863	4.5•	200	1.0	311	30
00826	5.5	125	1.0	243	36
00827	5.5•	175	1.0	293	36
00828	6.0•	150	1.2	268	36
00829	6.5	150	1.2	268	36
00830	8.0	175	1.2	299	41
00831	8.0	175	1.6	299	41
00832	10.0	200	1.6	324	41

• Additional dimension, Non-DIN size.



Wiha SoftFinish® electric.

- Safety when working with live equipment up to 1,000 V AC and 1,500 V DC
- Each screwdriver is individually tested in a water bath at 10,000 volts according to IEC 60900:2012
- Awarded the GS symbol for tested safety
- Multi-component SoftFinish® handle provides maximum user comfort

Applications on live equipment are subject to very special requirements. The focus is on absolute user safety and Wiha demonstrates this with a wealth of details.

The high quality blade insulation is moulded directly onto the blade and therefore guarantees safety when working on live equipment up to 1,500 V DC / 1,000 V AC. To maintain this safety, each screwdriver of the SoftFinish® electric series is individually tested in a water bath at 10,000 Volts according to IEC 60900:2012.

The roll-off protection and the special handle geometry offer optimum handling and electrical safety, even in critical applications.