

# Wiha SoftFinish® electric.

The safe and comfortable insulated VDE screwdriver.

## For Phillips, Pozidriv and TORX® screws.



1000 V  
IEC 60900:2012

**321N** SoftFinish® electric Phillips screwdriver.  
Individually tested protective insulation  
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN ISO 8764. Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	PH	PH	PH	PH	PH
00846	PH0	60	164	23	10
00847	PH1	80	191	30	10
00848	PH2	100	218	36	10
00849	PH3	150	268	41	10
00850	PH4	200	318	41	5



1000 V  
IEC 60900:2012

**324** SoftFinish® electric Pozidriv screwdriver.  
Individually tested protective insulation  
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN ISO 8764. Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	PZ	PZ	PZ	PZ	PZ
00877	PZ0	60	164	23	10
00878	PZ1	80	191	30	10
00879	PZ2	100	218	36	10
00880	PZ3	150	324	41	5



1000 V  
IEC 60900:2012

**325** SoftFinish® electric TORX® screwdriver.  
Individually tested protective insulation  
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Extra: Sizes T10 to T40 are in the 3251 series with the slimFix screwdrivers.

Order-No.	T	T	T	T	T
03760	T5	60	164	23	10
03761	T6	60	164	23	10
03762	T7	60	164	23	10
00881	T8	60	164	23	10
00882	T9	60	164	23	10

## For allen screws and internal square-drive screws.



1000 V  
IEC 60900:2012

**322** SoftFinish® electric hex nut driver.  
Individually tested protective insulation  
1,000 V AC, VDE and GS tested.

Blade: Chrome-vanadium steel, through hardened, black-finish.  
Insulation moulded directly onto blade.

Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 3125. Manufactured acc. to IEC 60900:2012.

Application: For external hex screws and hex nuts.

Order-No.	H	H	H	H	H	
00853	4	125	236	30	10,2	10
00855	5	125	236	30	11,2	10
00856	5.5	125	236	30	11,2	10
00857	6	125	236	30	12,2	10
00858	7	125	243	36	14,5	10
00859	8	125	243	36	15,2	10
00860	9	125	243	36	16,0	10
00861	10	125	243	36	17,2	10
00862	11	125	243	41	19,2	5
00863	12	125	243	41	20,2	5
00864	13	125	243	41	22,2	5
00865	14	125	243	41	23,2	5
00866	15	125	243	41	25,2	5
00867	16	125	243	41	25,2	5
00868	17	125	243	41	27,2	5



1000 V  
IEC 60900:2012

**323N** SoftFinish® electric hex screwdriver.  
Individually tested protective insulation  
1,000 V AC, VDE and GS tested.

Blade: Chrome-vanadium steel, through hardened, black-finish.  
Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For allen screws.

Order-No.	H	H	H	H	H
30361	2.5	75	179	23	10
30362	3.0	75	179	23	10
30363	4.0	75	186	30	10
30364	5.0	75	186	30	10
30365	6.0	100	218	36	10
30366	8.0	100	218	36	10



1000 V  
IEC 60900:2012

**358N** SoftFinish® electric square (Robertson) screwdriver.  
Individually tested protective insulation  
1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For fastening and unfastening internal square-drive (Robertson) screws.

Order-No.	R	R	R	R	R	
32396	Robertson 1	2.3	100	211	30	10
32397	Robertson 2	2.8	150	268	36	10