

Safety Notice:

When working with VDE tools, observe the national safety and accident prevention regulations!



For terminal screws (slotted/ Phillips).



△YEC 60900:2012

SoftFinish® electric Xeno.

For terminal screws (slotted/ Phillips).

Individually tested protective insulation 1,000 V AC, VDE and GS

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-

tection.

Order-No.

32281

Series

SB 327 S2 327

Manufactured acc. to IEC 60900:2012. Standards:

Application: For all work on or around electrical components up to 1,000 V AC.

No slipping and better torque transfer with terminal screws e.g. in

switch-cabinets, fuse boxes and terminal blocks.

Order-No.	⊕	= ■	==	-	
30716	SL/PH1	80	191	30	10
30715	SL/PH2	100	218	36	10

For terminal screws (slotted/ Pozidriv).



△YEC 60900:2012

SoftFinish® electric Xeno. 328

For terminal screws (slotted/ Pozidriv).

Individually tested protective insulation 1,000 V AC, VDE and GS

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

black-finish.

Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-

tection.

Manufactured acc. to IEC 60900:2012. Standards:

Application: For all work on or around electrical components up to 1,000 V AC.

No slipping and better torque transfer with terminal screws e.g. in

switch-cabinets, fuse boxes and terminal blocks.

Order-No.	₩	==	==	- ÷	
30700	SL/PZ1	80	191	30	10
30701	SL/PZ2	100	218	36	10



SL/PH1x80 SL/PH2x100



SoftFinish® electric Xeno screwdriver set, 2 pcs. SB 328 S2 For terminal screws (slotted/ Pozidriv).

Individually tested protective insulation 1,000 V AC, VDE and GS

tested. Blister packed.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

black-finish. Protective insulation moulded directly onto the blade.

Handle: Ergonomic Wiha SoftFinish® multi-component

handle with roll-off protection.

Standards: Manufactured acc. to IEC 60900:2012.

For all work on or around electrical components up to 1,000 V AC. Application:

Order-No.	Series				
32282	SB 328 S2			1	
●	328	SL/PZ1x80	SL/PZ2x100		