



LED T8 15k hrs Start Glass (CCG/Mains) (without starter) – Direct shipment from China

LED 8/T8SG TU 15k 0.6m/865/220-240V DS

93092520

Product information

The LED T8 Start Glass 15,000 hour range provides an attractive, entry-level alternative to standard Fluorescent T8 lamps. The innovative design delivers impressive light distribution and high efficiency, while at the same time ensuring rapid payback. Available in 60, and 120 and 150 cm lengths, the affordable LED T8 Start Glass brings the benefits of tubular LED lighting to a wider range of applications.

Application areas



Office



Hospitality



Industrial



Car park

Product data

Product Code	93092520
Bulb Shape	T8
Bulb Finish	Diffuse
Regulatory comment	CE certified
Bulb maximum overall diameter [mm]	28
Nominal Length [mm]	600
Maximum Overall Length [mm]	604
Net weight per piece [g]	110
Gross weight per piece [g]	150
Operating position	Universal
Mercury Content [mg]	No
RoHS compliant	Yes
Brand	Tungsrám
Cap/Base	G13

Performance data

Nominal/ Rated Beam Angle [°]	200°
Color consistency (SDCM)	<6 steps
Colour Code	865
Rated Lumens [lm]	800
Weighted energy consumption [kWh/1000h]	8.0
Rated efficacy [lm/W]	100
Energy efficiency class (EEC)	F
Rated life L70/B50 [h]	15000
Nominal correlated colour temperature (CCT) [K]	6500
Nominal lumens [lm]	800
Colour Rendering Index (CRI) [Ra]	80

Electrical data

Nominal lamp power factor...	>0,5
Rated power [W]	8.0
Lamp Current [A]	76mA
Design Ambient Temperature [°C]	-20...+40°C
Starting time (sec)	<0,5 sec
Number of switching cycles	30000
Dimming Capability	No
Nominal power [W]	8

Logistic data

Shipment	Direct shipment
DUN Code	20064894599754
EAN Code	0064894599750
Pack Quantity	15
Inner pack type	sleeve
Outer pack type	Bx
Layer quantity EUR	120
Layer quantity UK	150
Pallet quantity EUR (PC)	1200
Pallet quantity UK (PC)	1500
Outer case size	635x155x105mm
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

