



ST315



Safety transformer 63VA 230V12-24V

Technical properties

Architecture

Fixing mode DIN rail type O (symmetrical)

Configuration

Number of modules 6

Main electrical features

Rated operational voltage Ue 230 V

Frequency 50 Hz

Voltage

Rated insulation voltage 4000 V

Output voltage 2 24 V

Open circuit voltage secondary 14.2 / 26.5 V

Output voltage 12 / 24 V

Electric current

Output intensity 2 2.63 A

Output intensity 5.25 A

Dimensions

Depth of installed product 68 mm

Height of installed product 85 mm

Width of installed product 105 mm

Power

Power consumed 63 VA

Installation, mounting

Tightening torque 1,2Nm

Suitable for surface mounting Yes

Suitable for flush-mounting No

Mounting type din-Rail

Connection

Connection cross-sect. flexible conductor 4mm²

Connection cross-sect. rigid cable 6mm²

Cable

Max. cable length to door actuator release
0.5 A max. 100 m

Max. cable length to door actuator release 1
A

max. 50 m

Equipment

On/Off switch

No

Short-circuit protected

Yes

Standards

European directive WEEE

concerned

Safety

Protection index IP

IP20

Temperature protection

Yes

Use conditions

Operating temperature

-20...35 °C