

Single-socket plugs

British standard



Pack	Cat.Nos	British standard plugs
20	0 503 26	White 13 A - 250 V \sim - 2P+ \perp ASTA certification With integrated fuse for protection against overloads
20	6 500 13	13 A - 250 V \sim - 2P+ \perp With integrated fuse for protection against overloads
20	6 500 15	15 A - 250 V \sim - 2P+ \perp

Multi-socket plugs and extensions

German standard



Pack	Cat.Nos	2P multi-socket plugs - 6 A
10	0 506 50	For connection onto 2P+E socket Max. admissible power: 3.680 W at 230 V \sim 4 side outlets White
10	0 506 51	Black
5	Gencod labelling 0 504 90	2P+E multi-socket plugs - 16 A Max. admissible power 3.680 W at 230 V \sim 2 front outlets - shockproof IK 08 Rubber multi-socket plug with caps - IP 44 Black
10	Sleeve 0 506 55	2 front outlets White/Grey
10	0 505 11	Black
10	0 506 56	3 front outlets White/Grey
10	0 505 12	Black
10	0 506 62	3 side outlets White
10	0 506 63	Transparent
10	0 506 64	Alu/Black
10	3 902 33	2P+E extension leads With shutters for child protection to allow easy insert of the plug in the socket and to ensure safety 2P+E ergonomic socket with easy disconnection H05 VVF 3G 1.5 mm ² cord Supplied with plastic hook for hanging with Gencod 3 m length White
10	3 900 86	5 m length White
5	3 902 34	10 m length White
5	0 503 77	Multi-socket "octopus" extension leads ready to use - rubber Black - 2P+E - 16 A - IK 10 With 1 plug and 3 extensions H07 RNF 3G 1.5 and 2.5 mm ² cable Length: 0.8 m