

# 318.3246 CONNECTOR

32A 3P+E 6h 380-415V 50Hz 60Hz Screw terminals

### Product Approvals



CMIM  
MARQUAGE MAROC



I.M.Q. - ENEC 03  
European Norms Electrical Certification



CQC (China)  
China Quality Certification mark



EAC  
Eurasian Conformity



UE  
Declaration of conformity



TECHDATA		STANDARDS AND LAWS	
Type of product	CONNECTOR	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Commercial series	OPTIMA Series	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	CONNECTOR		
Mounting version	PORTABLE		
Rated current	32A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poles	3P+E	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Hour position	6h		
Rated voltage (range)	250-400V		
Rated voltage	380-415V	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Working frequency	60Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Working frequency	50Hz		
Colour	RED		
Protection degree	Watertight		
Protection degree IP	IP66/IP67/IP69	DIRECTIVE LOW VOLTAGE 2014/35	[European Directives] Low Voltage Directive

Types of available outlets	STRAIGHT	/UE
Terminals	Screw terminals	
Cable outlet	CABLE GLAND	