

# 318.6346 CONNECTOR

63A 3P+E 6h 380-415V 50Hz 60Hz Mantle terminals



## Product Approvals



CMIM  
MARQUAGE MAROC



I.M.Q. - ENEC 03  
European Norms Electrical Certification



CQC (China)  
China Quality Certification mark



EAC  
Eurasian Conformity



UE  
Declaration of conformity

| TECHDATA                |                | STANDARDS AND LAWS            |   |
|-------------------------|----------------|-------------------------------|---|
| Commercial series       | OPTIMA Series  | EN 60309-1 (1999)             | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Type of product         | CONNECTOR      | EN 60309-2 (1999)             | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | CONNECTOR      |                               |   |
| Mounting version        | PORTABLE       |                               |   |
| Rated current           | 63A            | EN 60309-1/A1 (2007)          | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Poles                   | 3P+E           | EN 60309-2/A1 (2007)          | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Hour position           | 6h             |                               |   |
| Rated voltage (range)   | 250-400V       |                               |   |
| Rated voltage           | 380-415V       | EN 60309-1/A2 (2012)          | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Working frequency       | 60Hz           | EN 60309-2/A2 (2012)          | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Working frequency       | 50Hz           |                               |   |
| Colour                  | RED            |                               |   |
| Protection degree       | Watertight     |                               |   |
| Protection degree IP    | IP66/IP67/IP69 | DIRECTIVE LOW VOLTAGE 2014/35 | [European Directives] Low Voltage Directive   |

|                            |                  |     |
|----------------------------|------------------|-----|
| Types of available outlets | STRAIGHT         | /UE |
| Terminals                  | Mantle terminals |     |
| Cable outlet               | CABLE GLAND      |     |
| Notes                      | EASY-PLUG        |     |