

518.6357T

SURFACE MOUNTING SOCKET

63A 3P+N+E 6h 346-415V 50Hz 60Hz Mantle terminals



Product Approvals



CMIM
MARQUAGE MAROC



I.M.Q. - ENEC 03
European Norms Electrical Certification



EAC
Eurasian Conformity



CQC (China)
China Quality Certification mark



UE
Declaration of conformity

TECHDATA

STANDARDS AND LAWS

Type of product	SURFACE MOUNTING SOCKET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Commercial series	OPTIMA-TOP Series	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	SURFACE MOUNTING SOCKET	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Mounting version	SURFACE MOUNTING	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Rated current	63A	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poles	3P+N+E	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Hour position	6h	DIRECTIVE LOW VOLTAGE 2014/35	[European Directives] Low Voltage Directive
Rated voltage (range)	250-400V		
Rated voltage	346-415V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	RED		
Protection degree	Watertight		
Protection degree IP	IP66/IP67/IP69		

Types of available outlets	ANGLED	/UE
Terminals	Mantle terminals	
Cable outlet	M40X1,5	