Product datasheet

Specification





undervoltage release, Acti9, iMN, voltage release, 220...240 V AC

A9A26960

Main

| Range Of Product | Acti9 |
|------------------------------|----------------------|
| Product Or Component Type | Undervoltage release |
| Device Short Name | iMN |
| [Uc] Control Circuit Voltage | 220240 V AC 50/60 Hz |
| Control Type | Standard |
| 9 Mm Pitches | 2 |

Complementary

| Range Compatibility | Acti 9 Acti9 iC65 Acti 9 Acti9 ARA Acti 9 Acti9 iDPN Vigi Acti 9 Acti9 iID Acti 9 Acti9 iSW-NA Acti 9 Acti9 iSW-NA Acti 9 Acti9 iDPN (China version) Acti 9 Acti9 iC60 double terminals miniature circuit breaker Acti 9 Acti9 iC40 |
|---|---|
| Local Signalling | Action indicator |
| Mounting Mode | Clip-on |
| Mounting Support | DIN rail |
| Comb Busbar And Distribution Block Compatibility | Top and bottom: YES |
| Width | 18 mm |
| Colour | White |
| Connections - Terminals | Clamp terminal - 1 cable(s) 8 mm² - rigid Clamp terminal - 2 cable(s) 2.7 mm² - rigid Clamp terminal - 1 cable(s) 6 mm² - flexible Clamp terminal - 2 cable(s) 2.7 mm² - flexible with cable end |
| Tightening Torque | 1 N.m |
| Compatibility Code | IMN |

Environment

| Standards | EN/IEC 60947-5-1 |
|---------------------------------------|----------------------------------|
| Tropicalisation | 2 conforming to EN/IEC 60947-5-1 |
| Relative Humidity | 95 % at 55 °C |
| Ambient Air Temperature For Operation | -3570 °C |
| Ambient Air Temperature For Storage | -4085 °C |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3 cm |
| Package 1 Width | 8 cm |
| Package 1 Length | 9.5 cm |
| Package 1 Weight | 81 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 8 |
| Package 2 Height | 8.7 cm |
| Package 2 Width | 10 cm |
| Package 2 Length | 26.7 cm |
| Package 2 Weight | 707 g |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 72 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 6.864 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |