



Acti9 iPB 1NC single push button red

A9E18031

Main

Range of product	Acti9
Product name	Acti9 iPB
Product or component type	Push-button
Device short name	iPB
Standards	IEC 60669-1 IEC 60947-5-1

Complementary

NC
0 A
50 V AC
push-button red
ixed
5 mm symmetrical DIN rail
pside: Clario pside: Librio pside: ProDis
2 mm
8 mm
1.5 mm
/hite
C-22: 30000 cycles AC 50/60 Hz
taggered tunnel terminal1 cable(s) 0.5 mm² rigid taggered tunnel terminal1 cable(s) 0.5 mm² flexible taggered tunnel terminal1 cable(s) 0.5 mm² flexible with ferrule taggered tunnel terminal2 cable(s) 2.5 mm² rigid taggered tunnel terminal2 cable(s) 2.5 mm² flexible taggered tunnel terminal2 cable(s) 2.5 mm² flexible taggered tunnel terminal2 cable(s) 2.5 mm² flexible with ferrule
mm

Environment

Tightening torque

Tropicalisation 2

1 N.m

Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-3570 °C
Ambient air temperature for storage	-4080 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	7.500 cm
Package 1 Length	9.000 cm
Package 1 Weight	39.300 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.000 cm
Package 2 Width	10.000 cm
Package 2 Length	23.500 cm
Package 2 Weight	527.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	5.162 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months

Recommended replacement(s)