

# Product data sheet

Specifications



## Acti9 iIL double indicator light - Green/Red - 110-230 Vac

A9E18325

### Main

Range of product	Acti9
Product name	Acti9 iIL
Product or component type	Modular pilot lighth
Device short name	iIL
[Us] rated supply voltage	110...230 V AC at 50/60 Hz 110...130 V DC

### Complementary

Indicator light	2 LEDs green/red, service life 100000 h of constant lighting efficiency (consumption 0.6 W)
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Comb busbar and distribution block compatibility	Upside: ProDis
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	69.5 mm
Colour	White (RAL 9003)
Auxiliary connection terminal	Tunnel type terminal 1 cable(s) rigid 0.5 mm <sup>2</sup> Tunnel type terminal 2 cable(s) rigid 2.5 mm <sup>2</sup> Tunnel type terminal 1 cable(s) flexible 0.5 mm <sup>2</sup> Tunnel type terminal 2 cable(s) flexible 2.5 mm <sup>2</sup> Tunnel type terminal 2 cable(s) flexible with ferrule 2.5 mm <sup>2</sup>
Wire stripping length	9 mm
Tightening torque	1 N.m

### Environment

Standards	IEC 60947-5-1
IP degree of protection	IP2 IPxx B
Pollution degree	2
Tropicalisation	2
Relative humidity	95 % at 55 °C

---

Ambient air temperature for operation	-35...70 °C
---------------------------------------	-------------

---

Ambient air temperature for storage	-40...80 °C
-------------------------------------	-------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	6.6 cm
------------------	--------

---

Package 1 Width	1.8 cm
-----------------	--------

---

Package 1 Length	8.2 cm
------------------	--------

---

Package 1 Weight	45 g
------------------	------

---

Unit Type of Package 2	BB1
------------------------	-----

---

Number of Units in Package 2	12
------------------------------	----

---

Package 2 Height	7.8 cm
------------------	--------

---

Package 2 Width	9.8 cm
-----------------	--------

---

Package 2 Length	23.3 cm
------------------	---------

---

Package 2 Weight	602 g
------------------	-------

---

Unit Type of Package 3	S03
------------------------	-----

---

Number of Units in Package 3	108
------------------------------	-----

---

Package 3 Height	30 cm
------------------	-------

---

Package 3 Width	30 cm
-----------------	-------

---

Package 3 Length	40 cm
------------------	-------

---

Package 3 Weight	5.906 kg
------------------	----------

## Offer Sustainability

---

Sustainable offer status	Green Premium product
--------------------------	-----------------------

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

---

Mercury free	Yes
--------------	-----

---

China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
-----------------------	---

---

RoHS exemption information	<a href="#">Yes</a>
----------------------------	---------------------

---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

---

Halogen content performance	Halogen free plastic parts & cables product
-----------------------------	---

## Contractual warranty

---

Warranty	18 months
----------	-----------

## Recommended replacement(s)