

# Product datasheet

Specifications



## iC60H - miniature circuit breaker - 1P - 2A - C curve

A9F84102

### Main

|                           |  |
|---------------------------|--|
| Device application        | Distribution   |
| Range                     | Acti9  |
| Product name              | Acti9 iC60   |
| Product or component type | Miniature circuit-breaker  |
| Device short name         | iC60H  |
| Poles description         | 1P   |
| Number of protected poles | 1  |
| [In] rated current        | 2 A  |
| Network type              | DC<br>AC   |
| Trip unit technology      | Thermal-magnetic   |
| Curve code                | C  |
| Breaking capacity         | 10000 A Icn at 230 V AC 50/60 Hz conforming to EN/IEC 60898-1<br>15 kA Icu at 60...72 V DC conforming to EN/IEC 60947-2<br>20 kA Icu at 12...60 V DC conforming to EN/IEC 60947-2<br>70 kA Icu at 12...60 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>70 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>70 kA Icu at 100...133 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| Utilisation category      | Category A conforming to EN 60947-2<br>Category A conforming to IEC 60947-2  |
| Suitability for isolation | Yes conforming to EN 60898-1<br>Yes conforming to EN 60947-2<br>Yes conforming to IEC 60898-1<br>Yes conforming to IEC 60947-2   |
| Standards                 | EN 60947-2<br>IEC 60947-2<br>IEC 60898-1<br>EN 60898-1   |

### Complementary

|                                       |  |
|---------------------------------------|--|
| Network frequency                     | 50/60 Hz   |
| Magnetic tripping limit               | 8 x In +/- 20 %  |
| [Ics] rated service breaking capacity | 70 kA 100 % conforming to EN 60947-2 - 12...60 V AC 50/60 Hz<br>70 kA 100 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz<br>70 kA 100 % conforming to IEC 60947-2 - 12...60 V AC 50/60 Hz<br>70 kA 100 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz<br>7500 A 75 % conforming to EN 60898-1 - 230 V AC 50/60 Hz<br>7500 A 75 % conforming to IEC 60898-1 - 230 V AC 50/60 Hz<br>70 kA 100 % conforming to IEC 60947-2 - 100...133 V AC 50/60 Hz<br>70 kA 100 % conforming to EN 60947-2 - 100...133 V AC 50/60 Hz<br>15 kA 100 % conforming to EN 60947-2 - 72 V DC |

15 kA 100 % conforming to IEC 60947-2 - 72 V DC  
 20 kA 100 % conforming to EN 60947-2 - 12...60 V DC  
 20 kA 100 % conforming to IEC 60947-2 - 12...60 V DC

|   |   |
|---|---|
| <b>Limitation class</b>                                 | 3 conforming to EN 60898-1<br>3 conforming to IEC 60898-1   |
| <b>[Ui] rated insulation voltage</b>                    | 500 V AC 50/60 Hz conforming to EN 60947-2<br>500 V AC 50/60 Hz conforming to IEC 60947-2                                       |
| <b>[Uimp] rated impulse withstand voltage</b>           | 6 kV conforming to EN 60947-2<br>6 kV conforming to IEC 60947-2   |
| <b>Contact position indicator</b>                       | Yes   |
| <b>Control type</b>                                     | Toggle  |
| <b>Local signalling</b>                                 | Trip indicator  |
| <b>Mounting mode</b>                                    | Fixed   |
| <b>Mounting support</b>                                 | DIN rail  |
| <b>Comb busbar and distribution block compatibility</b> | Top or bottom: YES  |
| <b>9 mm pitches</b>                                     | 2   |
| <b>Height</b>   | 85 mm   |
| <b>Width</b>  | 18 mm   |
| <b>Depth</b>  | 78.5 mm   |
| <b>Product weight</b>                                   | 0.215 kg  |
| <b>Colour</b>   | White   |
| <b>Mechanical durability</b>                            | 20000 cycles  |
| <b>Electrical durability</b>                            | 10000 cycles  |
| <b>Connections - terminals</b>                          | Single terminal (top or bottom) 1...25 mm <sup>2</sup> rigid<br>Single terminal (top or bottom) 1...16 mm <sup>2</sup> flexible |
| <b>Wire stripping length</b>                            | 14 mm for top or bottom connection  |
| <b>Tightening torque</b>                                | 2 N.m top or bottom   |
| <b>Earth-leakage protection</b>                         | Without   |

## Environment

|  |   |
|--|---|
| <b>IP degree of protection</b>               | IP20 conforming to IEC 60529<br>IP20 conforming to EN 60529 |
| <b>Pollution degree</b>                      | 3 conforming to EN 60947-2<br>3 conforming to IEC 60947-2   |
| <b>Overvoltage category</b>                  | IV  |
| <b>Tropicalisation</b>                       | 2 conforming to IEC 60068-1                                 |
| <b>Relative humidity</b>                     | 95 % at 55 °C   |
| <b>Operating altitude</b>                    | 0...2000 m  |
| <b>Ambient air temperature for operation</b> | -35...70 °C   |
| <b>Ambient air temperature for storage</b>   | -40...85 °C   |

## Packing Units

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type of Package 1</b>       | PCE      |
| <b>Number of Units in Package 1</b> | 1        |
| <b>Package 1 Height</b>             | 2.000 cm |
| <b>Package 1 Width</b>              | 7.500 cm |

|                              |           |
|------------------------------|-----------|
| Package 1 Length             | 9.500 cm  |
| Package 1 Weight             | 112.100 g |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 12        |
| Package 2 Height             | 8.000 cm  |
| Package 2 Width              | 10.000 cm |
| Package 2 Length             | 22.000 cm |
| Package 2 Weight             | 1.398 kg  |
| Unit Type of Package 3       | S03       |
| Number of Units in Package 3 | 132       |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 30.000 cm |
| Package 3 Length             | 40.000 cm |
| Package 3 Weight             | 15.769 kg |

## Offer Sustainability

|                             |   |
|-----------------------------|---|
| Sustainable offer status    | Green Premium product   |
| REACH Regulation            | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive           | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Mercury free                | Yes   |
| China RoHS Regulation       | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| RoHS exemption information  | <a href="#">Yes</a>   |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>   |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 12 months |
|----------|-----------|

## Recommended replacement(s)