

# Product datasheet

Specifications



## Miniature circuit-breaker, Acti9 iC60L, 1P, 25 A, C curve, 15000 A (IEC 60898-1), 25 kA (IEC 60947-2)

A9F94125

### Main

Device application	Distribution
Range	Acti9
Product name	Acti9 iC60
Product or component type	Miniature circuit-breaker
Device short name	iC60L
Poles description	1P
Number of protected poles	1
[In] rated current	25 A
Network type	AC DC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	15000 A Icn at 230 V AC 50/60 Hz conforming to EN/IEC 60898-1 50 kA Icu at 100...133 V AC 50/60 Hz conforming to EN/IEC 60947-2 70 kA Icu at 12...60 V AC 50/60 Hz conforming to EN/IEC 60947-2 20 kA Icu at 60...72 V DC conforming to EN/IEC 60947-2 25 kA Icu at 12...60 V DC conforming to EN/IEC 60947-2 25 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2
Utilisation category	Category A conforming to EN 60947-2 Category A conforming to IEC 60947-2
Suitability for isolation	Yes conforming to EN 60898-1 Yes conforming to EN 60947-2 Yes conforming to IEC 60898-1 Yes conforming to IEC 60947-2
Standards	EN 60898-1 EN 60947-2 IEC 60898-1 IEC 60947-2

### Complementary

Network frequency	50/60 Hz
Magnetic tripping limit	8 x In +/- 20 %
[Ics] rated service breaking capacity	12.5 kA 50 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz 12.5 kA 50 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz 35 kA 50 % conforming to EN 60947-2 - 12...60 V AC 50/60 Hz 35 kA 50 % conforming to IEC 60947-2 - 12...60 V AC 50/60 Hz 25 kA 50 % conforming to EN 60947-2 - 100...133 V AC 50/60 Hz 25 kA 50 % conforming to IEC 60947-2 - 100...133 V AC 50/60 Hz 7500 A 50 % conforming to EN 60898-1 - 230 V AC 50/60 Hz 7500 A 50 % conforming to IEC 60898-1 - 230 V AC 50/60 Hz 20 kA 100 % conforming to EN 60947-2 - 72 V DC

20 kA 100 % conforming to IEC 60947-2 - 72 V DC  
 25 kA 100 % conforming to EN 60947-2 - 12...60 V DC  
 25 kA 100 % conforming to IEC 60947-2 - 12...60 V DC

<b>Limitation class</b>	3 conforming to EN 60898-1 3 conforming to IEC 60898-1
<b>[Ui] rated insulation voltage</b>	500 V AC 50/60 Hz conforming to EN 60947-2 500 V AC 50/60 Hz conforming to IEC 60947-2
<b>[Uimp] rated impulse withstand voltage</b>	6 kV conforming to EN 60947-2 6 kV conforming to IEC 60947-2
<b>Contact position indicator</b>	Yes
<b>Control type</b>	Toggle
<b>Local signalling</b>	Trip indicator
<b>Mounting mode</b>	Fixed
<b>Mounting support</b>	DIN rail
<b>Comb busbar and distribution block compatibility</b>	Top or bottom: YES
<b>9 mm pitches</b>	2
<b>Height</b>	85 mm
<b>Width</b>	18 mm
<b>Depth</b>	78.5 mm
<b>Product weight</b>	0.215 kg
<b>Colour</b>	White
<b>Mechanical durability</b>	20000 cycles
<b>Electrical durability</b>	10000 cycles
<b>Connections - terminals</b>	Single terminal (top or bottom) 1...25 mm <sup>2</sup> rigid Single terminal (top or bottom) 1...16 mm <sup>2</sup> flexible
<b>Wire stripping length</b>	14 mm for top or bottom connection
<b>Tightening torque</b>	2 N.m top or bottom
<b>Earth-leakage protection</b>	Without

## Environment

<b>IP degree of protection</b>	IP20 conforming to IEC 60529 IP20 conforming to EN 60529
<b>Pollution degree</b>	3 conforming to EN 60947-2 3 conforming to IEC 60947-2
<b>Overvoltage category</b>	IV
<b>Tropicalisation</b>	2 conforming to IEC 60068-1
<b>Relative humidity</b>	95 % at 55 °C
<b>Operating altitude</b>	0...2000 m
<b>Ambient air temperature for operation</b>	-35...70 °C
<b>Ambient air temperature for storage</b>	-40...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	1.8 cm
<b>Package 1 Width</b>	7.5 cm

Package 1 Length	9.5 cm
Package 1 Weight	116.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.2 cm
Package 2 Width	9.8 cm
Package 2 Length	22.2 cm
Package 2 Weight	1.466 kg
Unit Type of Package 3	S03
Number of Units in Package 3	132
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	16.613 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)