

Product data sheet

Specifications



Fuse Disconnecter, Acti9 SBI, 1P, 50A, for fuse 14 x 51mm

A9GSB150

Main

Range	Acti9
Product name	Acti9 SBI
Product or component type	Fuse-disconnector
Device short name	SBI
Poles description	1P

Complementary

[In] rated current	10 A 12 A 16 A 20 A 25 A 32 A 40 A 50 A
Fuse curve	GG AM
Fuse size	14 x 51 mm
[Ue] rated operational voltage	690 V AC
Mounting support	35 mm symmetrical DIN rail
Locking options description	Non padlockable
9 mm pitches	3
Height	107 mm
Width	26.5 mm
Depth	70 mm
Connections - terminals	Screw clamp terminals1 cable(s) 2.5...25 mm ² rigid Screw clamp terminals1 cable(s) 2.5...25 mm ² flexible
Tightening torque	3.5 N.m

Environment

Standards	IEC EN 60947-3
Pollution degree	3
Ambient air temperature for operation	-20...60 °C

Ambient air temperature for storage	-40...80 °C
-------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	2.800 cm
------------------	----------

Package 1 Width	7.800 cm
-----------------	----------

Package 1 Length	11.400 cm
------------------	-----------

Package 1 Weight	119.000 g
------------------	-----------

Unit Type of Package 2	BB1
------------------------	-----

Number of Units in Package 2	6
------------------------------	---

Package 2 Height	8.500 cm
------------------	----------

Package 2 Width	12.000 cm
-----------------	-----------

Package 2 Length	17.400 cm
------------------	-----------

Package 2 Weight	793.000 g
------------------	-----------

Unit Type of Package 3	S03
------------------------	-----

Number of Units in Package 3	72
------------------------------	----

Package 3 Height	30.000 cm
------------------	-----------

Package 3 Width	30.000 cm
-----------------	-----------

Package 3 Length	40.000 cm
------------------	-----------

Package 3 Weight	9.976 kg
------------------	----------

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
-----------------------	---

RoHS exemption information	Yes
----------------------------	-----

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)