



Acti 9 - fuse-disconnector STI - 1 pole - 10 A - for fuse 8.5 x 31.5 mm

A9N15635

M	а	ı	r	

Range	Acti9
Product name	Acti9 STI
Product or component type	Fuse-disconnector
Device short name	STI
Poles description	1P

Complementary

Complementary			
[In] rated current	2 A 4 A 6 A 10 A		
Fuse curve	AM GG		
Fuse size	8.5 x 31.5 mm		
[Ue] rated operational voltage	400 V AC		
[Ui] rated insulation voltage	500 V AC 50/60 Hz		
Mounting mode	Clip-on		
Mounting support	DIN rail		
9 mm pitches	2		
Height	81 mm		
Width	18 mm		
Depth	75 mm		
Colour	White		
Connections - terminals	Screw clamp terminals1 cable(s) 0.7510 mm² rigid Screw clamp terminals1 cable(s) 0.56 mm² flexible Screw clamp terminals2 cable(s) 0.754 mm² rigid Screw clamp terminals2 cable(s) 0.56 mm² flexible		
Wire stripping length	12 mm		

Environment

Tightening torque

Standards	IEC EN 60947-3 IEC 60269-1/2
IP degree of protection	IP20

2 N.m

Pollution degree	3
Ambient air temperature for operation	-2060 °C
Ambient air temperature for storage	-4080 °C
Dooking Unito	

Packing Units

<u> </u>	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.8 cm
Package 1 Width	7.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	55 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.6 cm
Package 2 Width	9.2 cm
Package 2 Length	22.2 cm
Package 2 Weight	714 g
Unit Type of Package 3	S03
Number of Units in Package 3	144
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	9.055 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty 12 months

Recommended replacement(s)