Product data sheet

Specifications



Acti9 - comb busbar - 1L - 18 mm pitch - 12 modules - 100A



A9XPH112

| I | 71 | lċ | 1 | ı | ı | ı |
|---|----|----|---|---|---|---|
| | | | | | | |

| Range | Acti9 |
|------------------------------------|----------------------|
| Product or component type | Comb busbar |
| Mounting mode | Horizontal |
| Accessory / separate part category | Connection accessory |
| Lines description | 1L |
| Length in 18 mm modules | 12 |

Complementary

| Number of ways | 12 ways 1 L |
|--------------------------------|---|
| Poles configuration for 1 way | 1 x 1P |
| Connection pitch | 18 mm |
| Connector type | Tooth |
| Distance between way | 18 mm |
| Marking | L |
| Insulation | Insulated |
| Device presentation | Cuttable |
| [le] rated operational current | 100 A at 40 °C |
| [Ue] rated operational voltage | 415 V AC |
| [Ui] rated insulation voltage | 500 V AC conforming to IEC 61439-2 |
| Mounting location | Top or bottom on tunnel type terminals Top or bottom on double terminal |
| 9 mm pitches | 24 |
| Width | 220 mm |
| Colour | White (RAL 9003) |
| Range compatibility | Acti 9 (Acti9 iC60) Acti 9 (Acti9 iK60) Acti 9 (Acti9 iID) |

Acti 9 (Acti9 iID K) Acti 9 (Acti9 iSW) Acti 9 (Acti9 iSW-NA) Multi9 (Multi9 C60)

Environment

| Standards | IEC 60947-7-1 IEC 61439-2 |
|-------------------------|---|
| Fire resistance | 960 °C (30 s) conforming to IEC 60695-2-1 |
| Pollution degree | 3 conforming to IEC 60947-7-1 |
| IP degree of protection | IP20 with end-pieces and tooth covers |

Packing Units

| r doming office | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6 cm |
| Package 1 Width | 8.7 cm |
| Package 1 Length | 24.8 cm |
| Package 1 Weight | 49 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 6 cm |
| Package 2 Width | 8.7 cm |
| Package 2 Length | 24.8 cm |
| Package 2 Weight | 555 g |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 160 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 9.38 kg |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

Warranty 18 months

Recommended replacement(s)