

Product data sheet

Specifications



control relay, TeSys K, 4P(3NO +1NC), 690V, 110V AC coil

CA2KN31F7

Main

| | |
|--------------------------------|--|
| Range | TeSys |
| Product name | TeSys CAK |
| Product or component type | Control relay |
| Device short name | CA2K |
| Contact application | Control circuit |
| Utilisation category | AC-15 DC-13 |
| Pole contact composition | 3 NO + 1 NC |
| [Ue] rated operational voltage | $\leq 690 \text{ V} \leq 400 \text{ Hz}$ |
| Control circuit type | AC at 50/60 Hz |
| [Uc] control circuit voltage | 110 V AC 50/60 Hz |

Complementary

| | |
|---|--|
| [Ith] conventional free air thermal current | 10 A (at 50 °C) |
| Irms rated making capacity | 110 A conforming to IEC 60947 |
| Associated fuse rating | 10 A gG conforming to IEC 60947 10 A gG conforming to VDE 0660 |
| [Ui] rated insulation voltage | 690 V conforming to IEC 60947 750 V conforming to VDE 0110 group C 690 V conforming to BS 5424 600 V conforming to CSA C22.2 No 14 |
| Mounting support | Rail Plate |
| Connections - terminals | Screw clamp terminals 1 cable(s) 1.5...4 mm ² solid Screw clamp terminals 2 cable(s) 1.5...4 mm ² solid Screw clamp terminals 1 cable(s) 0.75...4 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 0.75...4 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 0.34...1.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 0.34...1.5 mm ² flexible without cable end |
| Tightening torque | 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm 1.3 N.m - on screw clamp terminals - with screwdriver Philips No 26 mm 1.3 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 |
| Control circuit voltage limits | Drop-out: 0.2...0.75 U _c (at <50 °C) Operational: 0.8...1.15 U _c (at <50 °C) |
| Operating time | 10...20 ms coil de-energisation and NO opening 10...20 ms coil energisation and NO closing 15...25 ms coil de-energisation and NC closing 5...15 ms coil energisation and NC opening |

| | |
|--|-------------------|
| Mechanical durability | 10 Mcycles |
| Maximum operating rate | 10000 cyc/h |
| Immunity to microbreaks | 2 ms |
| Inrush power in VA | 30 VA (at 20 °C) |
| Hold-in power consumption in VA | 4.5 VA (at 20 °C) |
| Heat dissipation | 1.3 W |
| Minimum switching voltage | 17 V |
| Minimum switching current | 5 mA |
| Non overlap distance | 0.5 mm |
| Insulation resistance | > 10 MOhm |
| Height | 58 mm |
| Width | 45 mm |
| Depth | 57 mm |
| Net weight | 0.18 kg |

Environment

| | |
|--|--|
| Standards | BS 5424 IEC 60947 NF C 63-140 VDE 0660 |
| Product certifications | UL CSA UKCA |
| IP degree of protection | IP2X |
| Protective treatment | TC conforming to IEC 60068 |
| Ambient air temperature for operation | -25...50 °C |
| Ambient air temperature for storage | -50...80 °C |
| Operating altitude | 2000 m without derating |
| Flame retardance | V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 |
| Mechanical robustness | Vibrations contactor open: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations contactor closed: 4 Gn, 5...300 Hz conforming to IEC 60068-2-6 Shocks contactor open: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed: 15 Gn for 11 ms conforming to IEC 60068-2-27 |

Packing Units

| | |
|-------------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.8 cm |
| Package 1 Width | 6.2 cm |
| Package 1 Length | 6.6 cm |
| Package 1 Weight | 178 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 50 |
| Package 2 Height | 15 cm |
| Package 2 Width | 30 cm |

| | |
|------------------|----------|
| Package 2 Length | 40 cm |
| Package 2 Weight | 9.281 kg |
| Package 3 Height | 77 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)