

# Product data sheet

Specifications



## Acti9 - IH - mechanical time switch - 24 h - without memory

CCT16364

### Main

Range of product	Acti9
Product name	Acti9 IH
Device short name	IH
Product or component type	Mechanical time switch
Number of channels	1
Function available	Manual time changeover

### Complementary

Device application	Building
Load type	230 V AC halogen lamp 1000 W 230 V AC incandescent lamp 1100 W 230 V AC fluocompact lamp 600 VA Parallel-corrected fluorescent tube 2 x electronic ballast 40 W 12 µF Compact fluorescent lampelectronic ballast 25 W LED lamp < 2 W 20 W LED lamp > 2 W 180 W
Cycle duration	24 h
Maximum number of switchings	48 on - 48 off
Minimum interval duration	15 min
Type of setting	Manual time changeover
Power consumption in W	0.5 W
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V AC at 50 Hz
Mounting support	DIN rail
9 mm pitches	6
Colour tint	White (RAL 9003)
Connections - terminals	Screwless terminals
Clamping connection capacity	2 x 0.5...2 .5 mm <sup>2</sup>
Width	54 mm
Height	90 mm
Depth	66 mm
Net weight	0.135 kg

Standards	EN 60730-1
-----------	------------

## Environment

Ambient air temperature for operation	-20...55 °C
IP degree of protection	IP20 conforming to EN 60529

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.8 cm
Package 1 Width	8.0 cm
Package 1 Length	10.6 cm
Package 1 Weight	201.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	36
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.737 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)