

# Product data sheet

Specifications



## Contactors, TeSys Deca, 4P(2NO +2NC), AC-1, <= 440V, 40A, 220V AC 50/60Hz coil, screw terminal

LC1D258M7

### Main

|                                |   |
|--------------------------------|---|
| Range of product               | TeSys Deca  |
| Product or component type      | Contactors  |
| Device short name              | LC1D  |
| Contactors application         | Resistive load  |
| Utilisation category           | AC-1<br>AC-3<br>AC-3e<br>AC-4                           |
| Poles description              | 4P  |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 25...400 Hz                  |
| [Ie] rated operational current | 40 A (at <=60 °C) at <= 440 V AC AC-1 for power circuit |
| [Uc] control circuit voltage   | 220 V AC 50/60 Hz                                       |

### Complementary

|   |   |
|---|---|
| Compatibility code                          | LC1D  |
| Pole contact composition                    | 2 NO + 2 NC   |
| Contact compatibility                       | M6  |
| Protective cover                            | With  |
| [Ith] conventional free air thermal current | 10 A (at 60 °C) for signalling circuit<br>40 A (at 60 °C) for power circuit   |
| Irms rated making capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>450 A at 440 V for power circuit conforming to IEC 60947  |
| Rated breaking capacity                     | 450 A at 440 V for power circuit conforming to IEC 60947  |
| [Icw] rated short-time withstand current    | 240 A 40 °C - 10 s for power circuit<br>380 A 40 °C - 1 s for power circuit<br>50 A 40 °C - 10 min for power circuit<br>120 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit |
| Associated fuse rating                      | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>63 A gG at <= 690 V coordination type 1 for power circuit<br>40 A gG at <= 690 V coordination type 2 for power circuit  |
| Average impedance                           | 2 mOhm - Ith 40 A 50 Hz for power circuit   |
| Power dissipation per pole                  | 3.2 W AC-1  |
| [Ui] rated insulation voltage               | Power circuit: 690 V conforming to IEC 60947-4-1  |

Power circuit: 600 V CSA certified  
 Power circuit: 600 V UL certified  
 Signalling circuit: 690 V conforming to IEC 60947-1  
 Signalling circuit: 600 V CSA certified  
 Signalling circuit: 600 V UL certified

|   |  |
|---|--|
| <b>Overvoltage category</b>                   | III  |
| <b>Pollution degree</b>                       | 3  |
| <b>[Uimp] rated impulse withstand voltage</b> | 6 kV conforming to IEC 60947   |
| <b>Safety reliability level</b>               | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1   |
| <b>Mechanical durability</b>                  | 15 Mcycles   |
| <b>Electrical durability</b>                  | 1.4 Mcycles 40 A AC-1 at $U_e \leq 440$ V  |
| <b>Control circuit type</b>                   | AC at 50/60 Hz   |
| <b>Coil technology</b>                        | Without built-in suppressor module   |
| <b>Control circuit voltage limits</b>         | 0.3...0.6 $U_c$ (-40...60 °C):drop-out AC 50/60 Hz<br>0.8...1.1 $U_c$ (-40...60 °C):operational AC 50 Hz<br>0.85...1.1 $U_c$ (-40...60 °C):operational AC 60 Hz  |
| <b>Inrush power in VA</b>                     | 70 VA 60 Hz $\cos \phi$ 0.75 (at 20 °C)<br>70 VA 50 Hz $\cos \phi$ 0.75 (at 20 °C)   |
| <b>Hold-in power consumption in VA</b>        | 7.5 VA 60 Hz $\cos \phi$ 0.3 (at 20 °C)<br>7 VA 50 Hz $\cos \phi$ 0.3 (at 20 °C)   |
| <b>Heat dissipation</b>                       | 2...3 W at 50/60 Hz  |
| <b>Operating time</b>                         | 12...22 ms closing<br>4...19 ms opening  |
| <b>Maximum operating rate</b>                 | 3600 cyc/h 60 °C   |
| <b>Connections - terminals</b>                | Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Power circuit: screw clamp terminals 1 2.5...10 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Power circuit: screw clamp terminals 2 2.5...10 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Power circuit: screw clamp terminals 1 2.5...10 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminals 2 2.5...10 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminals 1 2.5...16 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Power circuit: screw clamp terminals 2 2.5...16 mm <sup>2</sup> - cable stiffness: solid without cable end |
| <b>Tightening torque</b>                      | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2<br>Power circuit: 1.8 N.m - on screw clamps terminals - with screwdriver flat Ø 6 mm<br>Power circuit: 1.8 N.m - on screw clamps terminals - with screwdriver Philips No 2<br>Power circuit: 1.8 N.m - on screw clamp terminals - with screwdriver pozidriv No 2   |
| <b>Auxiliary contact composition</b>          | 1 NO + 1 NC  |
| <b>Auxiliary contacts type</b>                | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1   |
| <b>Signalling circuit frequency</b>           | 25...400 Hz  |
| <b>Minimum switching voltage</b>              | 17 V for signalling circuit  |
| <b>Minimum switching current</b>              | 5 mA for signalling circuit  |
| <b>Insulation resistance</b>                  | > 10 MOhm for signalling circuit   |
| <b>Non-overlap time</b>                       | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact  |
| <b>Mounting support</b>                       | Rail<br>Plate  |

## Environment

|                  |  |
|------------------|--|
| <b>Standards</b> | EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 60947-4-1<br>UL 60947-5-1 |
|------------------|--|

|  |   |
|--|---|
| <b>Product certifications</b>                                | UL<br>CSA<br>CCC<br>EAC<br>UKCA<br>CB<br>EU-RO-MR by DNV-GL   |
| <b>IP degree of protection</b>                               | IP20 front face conforming to IEC 60529   |
| <b>Protective treatment</b>                                  | TH conforming to IEC 60068-2-30   |
| <b>Climatic withstand</b>                                    | conforming to IACS E10 exposure to damp heat<br>conforming to IEC 60947-1 Annex Q category D exposure to damp heat  |
| <b>Permissible ambient air temperature around the device</b> | -40...60 °C<br>60...70 °C with derating   |
| <b>Operating altitude</b>                                    | 0...3000 m  |
| <b>Fire resistance</b>                                       | 850 °C conforming to IEC 60695-2-1  |
| <b>Flame retardance</b>                                      | V1 conforming to UL 94  |
| <b>Mechanical robustness</b>                                 | Vibrations contactor open (2 Gn, 5...300 Hz)<br>Vibrations contactor closed (4 Gn, 5...300 Hz)<br>Shocks contactor closed (15 Gn for 11 ms)<br>Shocks contactor open (8 Gn for 11 ms) |
| <b>Height</b>  | 91 mm   |
| <b>Width</b>   | 45 mm   |
| <b>Depth</b>   | 99 mm   |
| <b>Net weight</b>  | 0.425 kg  |

## Packing Units

|                                     |            |
|-------------------------------------|------------|
| <b>Unit Type of Package 1</b>       | Db         |
| <b>Number of Units in Package 1</b> | 1          |
| <b>Package 1 Height</b>             | 5.5 cm     |
| <b>Package 1 Width</b>              | 9.5 cm     |
| <b>Package 1 Length</b>             | 11.8 cm    |
| <b>Package 1 Weight</b>             | 470 g      |
| <b>Unit Type of Package 2</b>       | S02        |
| <b>Number of Units in Package 2</b> | 16         |
| <b>Package 2 Height</b>             | 15 cm      |
| <b>Package 2 Width</b>              | 30 cm      |
| <b>Package 2 Length</b>             | 40 cm      |
| <b>Package 2 Weight</b>             | 7.978 kg   |
| <b>Unit Type of Package 3</b>       | P06        |
| <b>Number of Units in Package 3</b> | 256        |
| <b>Package 3 Height</b>             | 75 cm      |
| <b>Package 3 Width</b>              | 60 cm      |
| <b>Package 3 Length</b>             | 80 cm      |
| <b>Package 3 Weight</b>             | 135.844 kg |

## Offer Sustainability

|                                 |                       |
|---------------------------------|-----------------------|
| <b>Sustainable offer status</b> | Green Premium product |
|---------------------------------|-----------------------|

|                                   |   |
|-----------------------------------|---|
| <b>REACH Regulation</b>           | <a href="#">REACH Declaration</a>   |
| <b>REACH free of SVHC</b>         | Yes   |
| <b>EU RoHS Directive</b>          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| <b>Toxic heavy metal free</b>     | Yes   |
| <b>Mercury free</b>               | Yes   |
| <b>China RoHS Regulation</b>      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)   |
| <b>RoHS exemption information</b> | Yes   |
| <b>Environmental Disclosure</b>   | <a href="#">Product Environmental Profile</a>   |
| <b>Circularity Profile</b>        | <a href="#">End of Life Information</a>   |
| <b>WEEE</b>                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins   |
| <b>PVC free</b>                   | Yes   |
| <b>California proposition 65</b>  | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| <b>Warranty</b> | 18 months |
|-----------------|-----------|

## Recommended replacement(s)