

Product datasheet

Specifications



TeSys LE - enclosed DOL starter - 8...11.5 A - 380 V AC coil

LE1M35Q716

Main

| | |
|-------------------------------------|--|
| Range | TeSys |
| Product name | TeSys LE |
| Device short name | LE1M |
| Product or component type | Enclosed DOL starter |
| Device application | Standard |
| Utilisation category | AC-3 |
| Device composition | Contactors Earth terminal Neutral terminal Thermal overload relay |
| Thermal protection adjustment range | 8...11.5 A |
| Motor power kW | 4 kW at 415 V AC 50/60 Hz 2.2 kW at 240 V AC 50/60 Hz 4 kW at 380/400 V AC 50/60 Hz 2.2 kW at 220/230 V AC 50/60 Hz |
| [Uc] control circuit voltage | 380 V AC 50/60 Hz |
| Control type | Push-button start green I Push-button stop/reset red O |

Complementary

| | |
|--------------------|---|
| Local signalling | Operating: LED (yellow) |
| Cable entry number | 2 ISO20 top 2 ISO25 top 2 Pg 13 top 2 Pg 21 top 2 ISO20 bottom 2 ISO25 bottom 2 Pg 13 bottom 2 Pg 21 bottom 2 Pg 16 top 2 Pg 16 bottom |
| Width | 78 mm |
| Height | 160 mm |
| Depth | 108 mm |
| Net weight | 0.6 kg |

Environment

| | |
|----------|---------------------------------------|
| Material | ABS (acrylonitrile butadiene-styrene) |
|----------|---------------------------------------|

| | |
|--|------------------------------|
| IP degree of protection | IP65 conforming to IEC 60529 |
| Standards | IEC 60947-4-1 |
| Ambient air temperature for operation | -5...40 °C |
| Environmental characteristic | Standard environment |
| product certifications | UKCA |

Packing Units

| | |
|-------------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.700 cm |
| Package 1 Width | 16.700 cm |
| Package 1 Length | 8.200 cm |
| Package 1 Weight | 572.000 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 3.774 kg |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
