Product datasheet

Specifications





MX shunt release, ComPacT NSX, rated voltage 380/415 VAC 50/60 Hz, 440/480 VAC 60 Hz, screwless spring terminal connections

Local distributor code:

391352700

LV429388

EAN Code: 3606480019104

Main

Range	ComPacT
Range Of Product	ComPact NSX100250
G	ComPacT NSX100250 new generation
	ComPact NSX400630
	ComPacT NSX400630 new generation
	ComPact NSX100250 DC
	ComPacT NSX100250 DC new generation
	ComPact NSX100250 DC PV
	ComPacT NSX100250 DC PV new generation
	ComPact NSX400630 DC
	ComPacT NSX400630 DC new generation
	ComPact NSX400630 DC PV
	ComPacT NSX400630 DC PV new generation
Device Short Name	MX
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Opening coil
	Shunt trip release
[Uc] Control Circuit Voltage	380415 V AC 50 Hz
	440480 V AC 60 Hz
Range Compatibility	ComPacT new generation ComPacT NSX new generation
	ComPacT new generation ComPacT NSX DC new generation
	ComPact ComPact NSX
	ComPact ComPact NSX DC
	EasyPact EasyPact CVS
	PowerPact PowerPact Multistandard

Complementary

Operating Threshold	0.71.1 x Un opening
Response Time	50 ms
Control Signal Type	Maintained Impulse
Impulse Duration	>= 20 ms
Supply Inrush Power	10 VA
Auxiliary Connection Terminal	Spring 0.51.5 mm² (AWG 20AWG 16)
Wire Stripping Length	7 mm

Packing Units

Unit Type Of Package 1 PCE

Number Of Units In Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	4.6 cm
Package 1 Length	6.0 cm
Package 1 Weight	114.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	7.0 cm
Package 2 Width	10.5 cm
Package 2 Length	23.6 cm
Package 2 Weight	1.189 kg
Unit Type Of Package 3	\$03
Number Of Units In Package 3	60
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	7.515 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more >





Transparency RoHS/REACh

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations