

Product datasheet

Specifications



MN undervoltage release - 200/250 V AC/DC - for MTZ fixed - spare part

LV833671SP

Main

Maximum Response Time	45 ms on opening for MasterPact MTZ1 95 ms on opening for MasterPact MTZ2 95 ms on opening for MasterPact MTZ3
Range	MasterPact
Device Short Name	MN
Product Or Component Type	Undervoltage release
Device Application	Safety
Range Compatibility	Masterpact MasterPact MTZ1 circuit breaker Masterpact MasterPact MTZ2 circuit breaker Masterpact MasterPact MTZ3 circuit breaker
Voltage Release Type	Instantaneous

Complementary

Control Type	Standard
[Un] Voltage Power Supply	200...250 V AC 50/60 Hz 200...250 V DC
Threshold Tripping Voltage	0.35...0.7 Un opening 0.85 Un closing
Holding Power Consumption	4.5 W
Circuit Breaker Mounting Mode	Fixed/drawout
Provided Equipment	1 instruction sheet
Offer Type	Spare part

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	3.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	236.0 g
Unit Type Of Package 2	S04
Number Of Units In Package 2	20
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm

Package 2 Length 60.0 cm

Package 2 Weight 4.954 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant](#)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)