

Distribution block, Linergy DX, 4P, 63A, 4 modules, 24 holes, quick connect bottom

LVS04041

Range	Linergy
Product or component type	Distribution block
Product name	Linergy DX
Range compatibility	Prisma PrismaSeT Pragma
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Location of connection	Bottom
Mounting support	DIN rail
Poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	6 kV
[le] rated operational current	63 A at 40 °C
[In] rated current	63 A at 40 °C
Connections - terminals	Supply: tunnel type terminal16 mm² (flexible) Supply: tunnel type terminal25 mm² (rigid) Distribution: spring terminal (phase) , 12 x 2.56 mm² (flexible) Distribution: spring terminal (phase) , 12 x 2.56 mm² (rigid) Distribution: spring terminal (neutral) , 12 x 2.56 mm² (flexible) Distribution: spring terminal (neutral) , 12 x 2.56 mm² (rigid)
9 mm pitches	8
Total number of 18 mm modules	4

Environment

Net weight

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 60947-7-1 IEC 61439-2

0.29 kg

	120 01 100 1	
Product certifications	ASEFA	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.700 cm
Package 1 Width	7.800 cm
Package 1 Length	10.200 cm
Package 1 Weight	312.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	9.883 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Recommended replacement(s)