

Product datasheet

Specifications



LINERGY DX 4P DIST.BLOCK 125A 6M 52HOLES

LVS04045

Main

Range	Lincery
Range Of Product	Lincery
Product Or Component Type	Distribution block
Product Name	Lincery DX
Range Compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure PrismaSeT Prisma PH enclosure PrismaSeT PrismaSeT Pack 250 enclosure
Accessory / Separate Part Category	Current distribution accessory
Ip Degree Of Protection	IPxx B

Complementary

Mounting Support	DIN rail
Installed Device	Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed C120 without earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle Acti 9: fixed iC120 without earth leakage protection - control: toggle ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS125 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation Multi9: fixed NG125 with earth leakage protection - control: toggle Multi9: fixed NG125 without earth leakage protection - control: toggle Multi9: fixed NG125 NA - control: toggle ComPact: fixed NG160 with earth leakage protection - control: toggle ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle ComPact: fixed NSXm without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSXm with earth leakage protection - control: toggle - vertical installation
Poles Description	4P
[Ue] Rated Operational Voltage	690 V AC
[Ui] Rated Insulation Voltage	750 V AC
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ie] Rated Operational Current	125 A at 40 °C
[Icw] Rated Short-Time Withstand Current	4.5 kA for 1 s
[Ipk] Rated Peak Withstand Current	20 kA
I²T On Activation	20250000 A².s

Connections - Terminals	Supply: tunnel type terminal 35 mm ² (rigid) Supply: tunnel type terminal 35 mm ² (flexible) Distribution: spring terminal, 2 x 4...10 mm ² (flexible) Distribution: spring terminal, 2 x 4...10 mm ² (rigid) Distribution: spring terminal, 3 x 2.5...6 mm ² (flexible) Distribution: spring terminal, 3 x 2.5...6 mm ² (rigid) Distribution: spring terminal, 7 x 1.5...4 mm ² (flexible) Distribution: spring terminal, 7 x 1.5...4 mm ² (rigid) Distribution: tunnel type terminal, 1 x 4...16 mm ² (flexible) Distribution: tunnel type terminal, 1 x 4...25 mm ² (rigid)
9 Mm Pitches	12
Height	127 mm
Width	108 mm
Depth	48 mm
Net Weight	0.5 kg
Colour	Anthracite grey (RAL 7016)

Environment

Pollution Degree	3
Resistance To Incandescent Wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 60947-7-1 IEC 61439-1, inside enclosure IEC 61439-2, inside enclosure
Product Certifications	ASTA
Ambient Air Temperature For Operation	-25...55 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.8 cm
Package 1 Width	11.2 cm
Package 1 Length	13.5 cm
Package 1 Weight	474 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	11.7 cm
Package 2 Width	15 cm
Package 2 Length	49.6 cm
Package 2 Weight	2.541 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	420
Package 3 Height	95 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	225 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

✓ Pvc Free

✓ Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

No need of specific recycling operations