



Main

Range of product	Mureva Styl
Product or component type	Socket-outlet
Device presentation	Complete product
Outlet poles configuration	2P + E
Outlet standard description	Side earth
Outlet standard	Schuko
Colour tint	Grey RAL 7016)

Complementary

Device mounting	Flush
Socket number	1
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/outdoor
Material	PP (polypropylene) Brass PC (polycarbonate)
Fixing mode	By screws
Clamping connection capacity	1...2.5 mm ² rigid 1...2.5 mm ² stranded 1...2.5 mm ² flexible
Wire stripping length	13 mm
Length	84 mm
Height	55 mm
Width	84 mm
Projecting depth	30 mm
Embedding depth	25 mm
Chemical and detergent products resistance	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

Quality labels	AENOR EAC
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing 650 °C IEC 60695-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	8,500 cm
Pakendi laius 1	8,500 cm
Pakendi pikkus 1	9,500 cm
Pakendi kaal 1	125,000 g
Pakendi tüüp 2	S04
Ühikute arv pakendis 2	60
Pakendi kõrgus 2	30,000 cm
Pakendi laius 2	40,000 cm
Pakendi pikkus 2	60,000 cm
Pakendi kaal 2	8,179 kg
Pakendi tüüp 3	P12
Ühikute arv pakendis 3	240
Pakendi kõrgus 3	45,000 cm
Pakendi laius 3	80,000 cm
Pakendi pikkus 3	120,000 cm
Pakendi kaal 3	44,716 kg

Offer Sustainability

Jätkusuutliku pakkumise olek	Green Premium toode
REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS Deklaratsioon
Elavhõbedavaba	Jah
Hiina EoHS regulatsioon	Hiina RoHS Deklaratsioon
RoHS eranditeave	Jah
Keskkonnaalane avaldus	Toote Keskkonnaprofiil