

Wall mounted polyester enclosure, Thalassa PLM, plain door, 747x536x300mm, IP66, IK10, RAL 7035

NSYPLM75G

١	V	1	а	ı	r

Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	747 mm
Nominal width	536 mm
Nominal depth	300 mm
Enclosure mounting	Wall mounted
Device composition	1 body 1 door 2 lock
Door type	Plain
Lock type	3 mm double-bar lock

#### Complementary

Number of locks	2
Mounting plate description	Without mounting plate
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	IEC 62208 NEMA classification 13 NEMA classification 4X
Product certifications	UL
Electrical insulation class	Class II

#### **Environment**

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Fire resistance	960 °C conforming to IEC 62208

Ambient air temperature for	-4080 °C
operation	

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	32.500 cm	
Package 1 Width	55.500 cm	
Package 1 Length	80.500 cm	
Package 1 Weight	14.781 kg	
Unit Tune of Deckors 2	PAM	
Unit Type of Package 2	PAW	
Number of Units in Package 2	12	
Number of Units in Package 2	12	
Number of Units in Package 2 Package 2 Height	12 220.000 cm	

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

### Recommended replacement(s)