

Pragma flush enclosure - IP40 - 3 x 18 modules - transparent door

PRA24318

Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	456 mm wall: 486 mm outside:
Height	630 mm wall: 660 mm outside:
Depth	86 mm wall: 43 mm outside:
Nb of 18 mm modules per row	18
Nb of horizontal rows	3
Electrical insulation class	Class II Double insulation
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of door	Transparent

Complementary

Complementary	
Enclosure mounting	Flush
9 mm pitches	36
Total number of 18 mm modules	54
Power dissipation in W	68 W
[In] rated current	125 A
Type of rail	DIN
Mounting plate description	Without mounting plate
Cable entry	Side pre-cutouts Removable plates Cable or tube
Number of terminal blocks	1 earth (Quick) with 24 outgoers 1 neutral (Quick) with 24 outgoers
Distribution block outgoers	3 x 25 mm² for earth 21 x 4 mm² for earth

Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

3 x 25 mm² for neutral

	21 x 4 mm² for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Colour	Enclosure: white (RAL 9016) Front face: grey (RAL 7004) Door: colourless
Market segment	Small commercial Residential
Embedding depth	86 mm
Internal depth	84 mm
Environment	
Fire resistance	Back part: 650 °C Front face: 650 °C Door: 650 °C
IP degree of protection	IP30 without door IP40 with door
IK degree of protection	IK08 without door IK09 with door
Overvoltage category	II
Ambient air temperature for operation	-2560 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.000 cm
Package 1 Width	50.000 cm
Package 1 Length	
	68.000 cm
Package 1 Weight	68.000 cm 6.371 kg
Package 1 Weight Unit Type of Package 2	
	6.371 kg
Unit Type of Package 2	6.371 kg P12
Unit Type of Package 2 Number of Units in Package 2	6.371 kg P12 10
Unit Type of Package 2 Number of Units in Package 2 Package 2 Height	6.371 kg P12 10 160.000 cm
Unit Type of Package 2 Number of Units in Package 2 Package 2 Height Package 2 Width	6.371 kg P12 10 160.000 cm 80.000 cm
Unit Type of Package 2 Number of Units in Package 2 Package 2 Height Package 2 Width Package 2 Length	6.371 kg P12 10 160.000 cm 80.000 cm
Unit Type of Package 2 Number of Units in Package 2 Package 2 Height Package 2 Width Package 2 Length Package 2 Weight	6.371 kg P12 10 160.000 cm 80.000 cm
Unit Type of Package 2 Number of Units in Package 2 Package 2 Height Package 2 Width Package 2 Length Package 2 Weight Offer Sustainability	6.371 kg P12 10 160.000 cm 80.000 cm 120.000 cm 75.710 kg
Unit Type of Package 2 Number of Units in Package 2 Package 2 Height Package 2 Width Package 2 Length Package 2 Weight Offer Sustainability Sustainable offer status	6.371 kg P12 10 160.000 cm 80.000 cm 120.000 cm 75.710 kg
Unit Type of Package 2 Number of Units in Package 2 Package 2 Height Package 2 Width Package 2 Length Package 2 Weight Offer Sustainability Sustainable offer status REACh Regulation	6.371 kg P12 10 160.000 cm 80.000 cm 120.000 cm 75.710 kg Green Premium product REACh Declaration

Pro-active China RoHS declaration (out of China RoHS legal scope)

Yes

Mercury free

China RoHS Regulation

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Contractual warranty	
Warrantv	18 months