

Pragma surface enclosure - IP30 - 2 x 18 modules - transparent door

PRA29218

Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	426 mm outside:
Height	450 mm
Depth	145 mm
Nb of 18 mm modules per row	18
Nb of horizontal rows	2
Electrical insulation class	Double insulation Class II
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of door	Transparent

Complementary

Enclosure mounting	Surface
9 mm pitches	36
Total number of 18 mm modules	36
Power dissipation in W	50 W
[In] rated current	90 A
Type of rail	DIN
Mounting plate description	Without mounting plate
Cable entry	Cable or tube Removable plates Cut-out plates Trunking
Number of terminal blocks	1 earth (Quick) with 24 outgoers 1 neutral (Quick) with 24 outgoers
Distribution block outgoers	3 x 25 mm² for earth 21 x 4 mm² for earth 3 x 25 mm² for neutral

21 x 4 mm² for neutral

Back part: technoplastic Front face: technoplastic
Enclosure: white (RAL 9016) Front face: grey (RAL 7004) Door: colourless
Residential Small commercial
0 mm
95 mm
Back part: 650 °C Front face: 650 °C Door: 650 °C
IP30 without door IP40 with door
IK08 without door IK09 with door
II
-2560 °C
IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3
PCE
1
18.5 cm
51.0 cm
53.0 cm
4.7 kg
Green Premium product
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Yes
Yes
China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Yes
Product Environmental Profile
18 months