Product data sheet

Specifications

Sreen Premium™



Socket, Harmony, for RPM1 power relays, 16A screw clamp terminals, mixed contact

RPZF1

Main	
Range of product	Harmony Electromechanical Relays
Product or component type	Socket
Contact terminal arrangement	Mixed
Product compatibility	Plug-in relay RPM with 1 C/O contact
Device short name	RPZ
Complementary	
[lth] conventional free air thermal current	16 A
[Ue] rated operational voltage	250 V
Tightening torque	< 1 N.m for M3.5 screw(s) < 0.8 N.m for M3 screw(s)
Fixing mode	By screw (panel) Clip-on (35 mm symmetrical DIN rail)
Net weight	0.031 kg
[Uimp] rated impulse withstand voltage	4 kV
Overvoltage category	III
Pollution degree	3

Environment

Connections - terminals	Contact terminal - screw clamp terminals, 2 wires solid cable without cable end 0.54 mm ² / AWG 20AWG 12
	Contact terminal - screw clamp terminals, 1 wire solid cable without cable end 0.54 mm² / AWG 20AWG 12
	Contact terminal - screw clamp terminals, 2 wires flexible cable with cable end 0.52.5 mm² / AWG 20AWG 14
	Contact terminal - screw clamp terminals, 1 wire flexible cable with cable end 0.52.5 mm² / AWG 20AWG 14
	Coil terminal - screw clamp terminals, 2 wires solid cable without cable end 0.52.5 mm² / AWG 20AWG 14
	Coil terminal - screw clamp terminals, 1 wire solid cable without cable end 0.52.5 mm² / AWG 20AWG 14
	Coil terminal - screw clamp terminals, 2 wires flexible cable with cable end 0.51.5 mm² / AWG 20AWG 16
	Coil terminal - screw clamp terminals, 1 wire flexible cable with cable end 0.51.5 mm² / AWG 20AWG 16
Standards	IEC 61984 CSA C22.2 No 14 UL 508
Product certifications	CSA UL



	EAC CE
Ambient air temperature for storage	-4085 °C
Ambient air temperature for operation	-4055 °C
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

Packing Units

-	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	2.1 cm
Package 1 Length	8.5 cm
Package 1 Weight	30 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6.5 cm
Package 2 Width	9 cm
Package 2 Length	10.7 cm
Package 2 Weight	335 g
Unit Type of Package 3	S03
Number of Units in Package 3	240
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	8.593 kg

Offer Sustainability

3	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty


18 months



Product data sheet

Dimensions Drawings


Dimensions



Product data sheet

Connections and Schema

Wiring Diagram



Symbols shown in blue correspond to Nema marking.

Recommended replacement(s)