



TECHNICAL FEATURES

Colour: Grey or Black

Compliant with RoHS
Halogen-free polyester (PET) monofilament
Diameter 0.22 mm

Density: 1.14 kg/dm³

Working temperature: - 50°C + 150°C

Melting temperature: 230± 5°C

Self-extinguishing: UL 94-V2
Flame retardant

Packaging: coil in cardboard box self-reeling from the center

POLYESTER BRAIDED SLEEVE V2 UL - Grey colour

| Code | Reference | | ø nom. (mm) | ø min (mm) | ø max (mm) |
|----------------|-----------|-------|-------------|------------|------------|
| GPG2001 | GPG 04G | 100 m | 4 | 2 | 7 |
| GPG2000 | GPG 06G | 100 m | 6 | 3 | 9 |
| GPG2005 | GPG 08G | 100 m | 8 | 5 | 14 |
| GPG2010 | GPG 10G | 100 m | 10 | 7 | 17 |
| GPG2015 | GPG 12G | 50 m | 12 | 8 | 24 |
| GPG2020 | GPG 15G | 50 m | 15 | 10 | 27 |
| GPG2025 | GPG 20G | 50 m | 20 | 14 | 30 |
| GPG2029 | GPG 25G | 50 m | 25 | 17 | 40 |
| GPG2030 | GPG 30G | 50 m | 30 | 20 | 50 |
| GPG2034 | GPG 35G | 50 m | 35 | 25 | 55 |
| GPG2035 | GPG 40G | 50 m | 40 | 30 | 60 |
| GPG2040 | GPG 50G | 50 m | 50 | 40 | 80 |
| GPG2045 | GPG 64G | 25 m | 64 | 45 | 105 |

POLYESTER BRAIDED SLEEVE V2 UL - Black colour

| Code | Reference | | ø nom (mm) | ø min (mm) | ø max (mm) |
|----------------|-----------|-------|------------|------------|------------|
| GPN2001 | GPN 04N | 100 m | 4 | 2 | 7 |
| GPN2000 | GPN 06N | 100 m | 6 | 3 | 9 |
| GPN2005 | GPN 08N | 100 m | 8 | 5 | 14 |
| GPN2010 | GPN 10N | 100 m | 10 | 7 | 17 |
| GPN2015 | GPN 12N | 50 m | 12 | 8 | 24 |
| GPN2020 | GPN 15N | 50 m | 15 | 10 | 27 |
| GPN2025 | GPN 20N | 50 m | 20 | 14 | 30 |
| GPN2029 | GPN 25N | 50 m | 25 | 17 | 40 |
| GPN2030 | GPN 30N | 50 m | 30 | 20 | 50 |
| GPN2034 | GPN 35N | 50 m | 35 | 25 | 55 |
| GPN2035 | GPN 40N | 50 m | 40 | 30 | 60 |
| GPN2040 | GPN 50N | 50 m | 50 | 40 | 80 |
| GPN2045 | GPN 64N | 25 m | 64 | 45 | 105 |