

ZCKE05

Limit switch head, Limit switches XC Standard,
ZCKE, without lever left and right actuation



Main

| | |
|---------------------------|--|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch head |
| Device short name | ZCKE |
| Head type | Rotary head |
| Product compatibility | XCKJ |
| Associated lever | ZCKY91 ZCKY52 ZCKY53 ZCKY11 ZCKY13 ZCKY43 ZCKY51 ZCKY14 ZCKY81 ZCKY41 ZCKY59 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|----------------------------|--|
| Associated body | ZCKJD37H7 ZCKJ5H29 ZCKJ8H7 ZCKJ1H29 ZCKJ8 ZCKJ7 ZCKJ41 ZCKJ6H29 ZCKJ11H29 ZCKJ41H29 ZCKJ11H7 ZCKJD35H7 ZCKJD31H7 ZCKJ9H29 ZCKJD31H29 ZCKJ21 ZCKJD39H7 ZCKJ9H7 ZCKJ4H29 ZCKJD35H29 ZCKJ6 ZCKJ11 ZCKJ5 ZCKJ7H29 ZCKJ1H7 ZCKJ7H7 ZCKJ9 ZCKJ8H29 ZCKJ6H7 ZCKJ4104H29 ZCKJD31 ZCKJ4104H7 ZCKJ5H7 ZCKJ2H7 ZCKJ404H29 ZCKJD37H29 ZCKJ4 ZCKJ21H7 ZCKJ1 ZCKJ2H29 ZCKJD39H29 ZCKJD37 ZCKJ2 ZCKJD35 ZCKJ41H7 ZCKJ404 ZCKJD39 ZCKJ4104 ZCKJ21H29 ZCKJ4H7 ZCKJ404H7 |
| Movement of operating head | Rotary |
| Type of operator | Without operating lever spring return |
| Type of approach | Lateral approach, 1 or 2 programmable direction |

Complementary

| | |
|------------------|---|
| Switch actuation | From left and/or right CW and/or CCW |
| Positive opening | With |
| Head material | Metal |

Environment

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.200 cm |
| Package 1 Width | 4.600 cm |
| Package 1 Length | 8.700 cm |
| Package 1 Weight | 168.000 g |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 27 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 15.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 4.794 kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 864 |
| Package 3 Height | 75.000 cm |
| Package 3 Width | 60.000 cm |
| Package 3 Length | 80.000 cm |
| Package 3 Weight | 160.852 kg |

Offer Sustainability

| | |
|--|--|
| Sustainable offer status | Green Premium product |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|