

# UT39C/UT39E

## SPECIFICATIONS

Basic Functions	Range	Best Accuracy	
		UT39C	UT39E
DC Voltage	200mV/2V/20V/200V/∞00V	±(0.5%+∞)	±(0.05%+3)
AC Voltage	2V/20V/200V/750V	±(0.8%+3)	±(0.5%+∞)
DC Current	2mA/200mA/20A	±(∞.8%+∞)	±(0.5%+5)
AC Current	2mA/200mA/20A	±(∞.8%+∞)	±(0.8%+5)
Resistance	200Ω/2kΩ/20kΩ/2MΩ/20MΩ	±(0.8%+∞)	±(0.3%+∞)
Capacitance	2nF/200nF/20μF 2nF/20nF/200nF/20μF	±(4%+3)	±(4%+3)
Temperature(°C)	-40°C~∞00°C	±(2%+8)	
Frequency	2kHz/20kHz	±(∞.5%+5)	±(∞.5%+5)
Special Functions			
Diode		✓	✓
Continuity Buzzer		✓	✓
Transistor		✓	✓
Sleep Mode		✓	✓
Low Battery Display		✓	✓
Input Impedance for DC Voltage Measurement	Around ∞0MΩ	✓	✓
Max. Display		∞999	∞9999

## GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	6∞ x 32 mm
Product Colour	<b>UT39C/UT39E</b> - Grey Hoister - Red
Product Net Weight	3∞0g (including Hoister)
Product Size	∞72 x 83 x 38 mm
Standard Accessories	<b>UT39C</b> - Test Lead, Battery, English Manual; Point Contact Temperature Probe, Hoister <b>UT39E</b> - Test Lead, Battery, English Manual, Hoister
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	598 x 4∞8 x 340 mm (0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	22kg



UT39C

**NEW**



UT39E

CE