

Series of chemical products in spray package designed to satisfy the different needs of installation and of the maintenance of electromechanical, electrical and electronic equipment.



- Container under pressure. Keep away from sunlight and do not expose to temperature exceeding 50° C. Do not perforate or burn even after use.
- Do not spray the product onto flames or red hot objects
- Keep away from sources of ignition. Do not smoke
- Keep away from children
- Do not breathe gas/fume/vapour/aerosol
- Take precautionary measures against static discharges
- Use only in well ventilated place



Code	Model	Description	Format (ml)
VE491700	C01	Unblocker - Lubricant - Waterproof - Cleaner	400
VE492500	C02	Cleaner - Sanitizer for air conditioners	400
VJ90280000	C03	Compressed air	400
VJ90020000	C04	Clean dry contacts	200
VJ90100000	C05	Lubricating contact cleaner	200
VE494100	C06	Universal lubricant	400
VE493300	C07	Silicone based oil - Lubricant	400
VE495800	C08	Professional zinc 98%	400
VE500500	C10/R	Marker (red)	400
VE499000	C10/G	Marker (yellow)	400
VE498200	C10/B	Marker (blue)	400
VE502100	C10/N	Marker (black)	400

C01 UNBLOCKER-LUBRICANT-WATERPROOF-CLEANER

Penetrates attacking rust and any other type of oxidation by unlocking the rusted, blocked or frozen parts.
Forms over time a protective film against water, ice, humidity and oxidation.



H222 - H229 - H315 - H336 - H411
P210 - P211 - P251 - P264 - P280 - P304+P340 - P312 - P410+P412

C02 CLEANER- SANITIZER FOR AIR CONDITIONERS

Sanitizing, specific product for cleaning civil and auto air-conditioning systems.



H222 - H229 - H319
P210 - P211 - P251 - P264 - P280 - P305+P351+P338 - P337+P313 - P410

C03 COMPRESSED AIR

Used for PC keyboards, printers, videos, electronic components, boiler burners to remove dust from small areas. To clean holes made in cement, or drain pipes etc.



H222 - H229
P210 - P211 - P251 - P410+P412

C04 CLEAN DRY CONTACTS

Dielectric up to 50000 volts.
Cleans and deoxidizes electrical contacts, circuits and boards. Does not damage paints or plastic surfaces.
Dries immediately.



H222 - H229 - H361f - H373 - H315 - H336 - H411
P210 - P211 - P251 - P273 - P280 - P410+P412

C05 LUBRICATING CONTACT CLEANER

Dielectric up to 50000 volts.
Cleans and deoxidizes electrical contacts, circuits and boards. Does not damage paints or plastic surfaces.
Leaves a light protective film.



H222 - H229
P210 - P211 - P251 - P301+P310 - P331 - P410+P412

C06 UNIVERSAL LUBRICANT

Resistant to temperatures up to 300°C and allows long intervals between a lubrication and the other one.
Assures a clean lubrication, anti-adhesive for dust and resistant to water.
Does not damage the o-rings.



H222 - H229 - H411
P210 - P211 - P251 - P273 - P391 - P410+P412

C07 SILICONE BASED OIL – LUBRICANT

Excellent anti-creaking effect.
Creates a water-repellent and antioxidant protection on metals, steel, rubberized fabrics, etc..
It is odourless and colourless, it preserves both at low temperatures (-38°C) and at high temperatures (+270°C). Polishes any material made of rubber, plastic, skin, wood, etc...



H222 - H229
P210 - P211 - P251 - P410+P412

C08 PROFESSIONAL ZINC 98%

Cold galvanizing for quick drying to protect against oxidation and rust.
Zinc 98% assures brilliant coverage over time, dries quickly and does not wipe.
The treated surface can be painted



H222 - H229 - H315 - H319 - H411
P210 - P211 - P251 - P280 - P303+P352 - P332+P313 - P410+P412

C10 MARKER (RED), (YELLOW), (BLUE), (BLACK)

100% acrylic line marking paint for horizontal and vertical applications. Indicated for factories, indications of various kinds, industrial floors, on cement, on sand etc...



H222+H229 - H315 - H319 - H336
P102 - P210 - P211 - P251 - P261 - P410+P412

H222 Extremely flammable aerosol. - **H222+H229** Extremely flammable aerosol. Pressurized container: may burst if heated. - **H229** Pressurized container: may burst if heated. - **H315** Causes skin irritation. - **H319** Causes serious eye irritation. - **H336** May cause drowsiness or dizziness. **H361f** Suspected of damaging fertility. - **H373** May cause damage to organs through prolonged or repeated exposure.

- **H411** Toxic to aquatic life with long lasting effects.

P101 If medical advice is needed, have product container or label at hand - **P102** Keep out of reach of children. - **P103** Read label before use. - **P210** Keep away from heat/sparks/open flames/hot surfaces. No smoking. - **P211** Do not spray on an open flame or other ignition source. - **P251** Pressurized container: do not pierce or burn, even after use. Avoid breathing dust / fume / gas / mist / vapors / aerosols.

P264 Wash ... thoroughly after handling - **P271** Use only outdoors or in a well-ventilated area. - **P273** Avoid release to the environment. - **P280** Wear protective gloves / protective clothing / eye protection / face protection. - **P301+P310** IF SWALLOWED: immediately contact a POISON CENTER/doctor/... - **P302+P352** IF ON SKIN: Wash with plenty of soap and water. - **P304+P340** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. - **P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. - **P312** Call a POISON CENTER or doctor/physician if you feel unwell. **P331** DO NOT induce vomiting. - **P332+P313** If skin irritation occurs: Get medical advice/attention. - **P337+P313** If eye irritation persists: Get medical advice/attention. - **P391** Collect spillage. - **P405** Store locked up. - **P410+P412** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. - **P501** Dispose of contents/container in accordance with applicable regulations.